

eRules

CERTIFICATION SPECIFICATIONS

(CS + AMC/GM)



Easy Access Rules for Normal-Category Aeroplanes (CS-23)

CS Amendment 6, AMC/GM Issue 5

EASA eRULES

EASA eRules: aviation rules for the 21st century

Rules are the core of the EU civil aviation system. The aim of the EASA eRules project is to make them accessible to stakeholders in an efficient and reliable way.

EASA eRules is a comprehensive, single system for structuring, sharing, and storing of rules. It is the single, easy-access online database for all aviation safety rules applicable to persons and organisations subject to Basic Regulation ([Regulation \(EU\) 2018/1139](#)).

The Easy Access Rules (EAR) are the output of the eRules project. The EAR books are consolidated versions of those rules, combining EU regulations with the related EASA Executive Director (ED) decisions in an easy-to-read format with advanced navigation features through links and bookmarks. The EAR books are regularly updated, following the adoption of an official publication.

The EAR books are available:

- in PDF format;
- as dynamic online publications with optimised performance for fast and seamless navigation, permalinks of all rule articles, as well as a wide range of functionalities, such as filters to obtain regulatory material tailored to one's needs, a search function through the table of contents to quickly access the relevant sections, and easy navigation for computers, tablets, and mobiles; and
- in XML (machine-readable) format that can be easily processed and automated by recipients, producing output that is compatible and can be synchronised with local applications, search databases, etc.

The EASA eRules system is developed and implemented in close cooperation with the Member States and aviation industry to ensure that all its capabilities are relevant and effective.

Published May 2026¹

Copyright notice

© European Union, 1998-2026

Unless otherwise specified, you can re-use the legal documents published in EUR-Lex for commercial or non-commercial purposes [...] ('© European Union, <http://eur-lex.europa.eu>, 1998-2026')².

¹ The published date represents the date when the consolidated version of the EAR book was generated.

² Euro-Lex, Important Legal Notice: <http://eur-lex.europa.eu/content/legal-notice/legal-notice.html>.

DISCLAIMER

This document is issued by the European Union Aviation Safety Agency (referred to as both 'EASA' and 'the Agency') to provide its stakeholders with an updated, consolidated, and easy-to-read publication. It has been prepared by putting together the officially published EU regulations with the related EASA certification specifications (CSs), acceptable means of compliance (AMC) and guidance material (GM) (including their amendments) adopted so far. However, this document is not an official publication, and EASA accepts no liability for damage of any kind resulting from the risks inherent in its use.

NOTE FROM THE EDITOR

The content of this document is arranged as follows: certification specifications (CSs), followed by the related acceptable means of compliance (AMC) and guidance material (GM).

All elements (i.e. CSs, AMC and GM) are colour-coded and can be identified according to the illustration below. The EASA Executive Director (ED) decision through which the CS, AMC, or GM was introduced or last amended is indicated below the CS, AMC, or GM title in *italics*.

Certification specification

ED decision

Acceptable means of compliance

ED decision

Guidance material

ED decision

This document will be updated regularly to incorporate further amendments.

The format of this document has been adjusted to make it user-friendly and for reference purposes. Any comments should be sent to erules@easa.europa.eu.

INCORPORATED AMENDMENTS

CS (ED DECISIONS)

Incorporated ED Decision	CS/AMC Issue No, Amendment No	Applicability date
ED Decision 2003/14/RM	CS-23/ Initial issue	14/11/2003
ED Decision 2009/001/R	CS-23/ Amendment 1	12/2/2009
ED Decision 2010/008/R	CS-23/ Amendment 2	28/9/2010
ED Decision 2012/012/R	CS-23/ Amendment 3	20/7/2012
ED Decision 2015/018/R	CS-23/ Amendment 4	17/7/2015
ED Decision 2017/013/R	CS-23/ Amendment 5	15/8/2017
ED Decision 2023/002/R	CS-23/ Amendment 6	8/3/2023

AMC/GM (ED DECISIONS)

Incorporated ED Decision	AMC/GM Issue No, Amendment No	Applicability date
ED Decision 2017/025/R	AMC & GM to CS-23/ Issue 1	21/12/2017
ED Decision 2019/020/R	AMC & GM to CS-23/ Issue 2	9/10/2019
ED Decision 2020/006/R	AMC & GM to CS-23/ Issue 3	1/1/2021
ED Decision 2023/002/R	AMC & GM to CS-23/ Issue 4	8/3/2023
ED Decision 2025/019/R	AMC & GM to CS-23/ Issue 4 - correction	1/10/2025
ED Decision 2026/003/R	AMC & GM to CS-23 / Issue 5	16/4/2026

Note: To access the official versions, please click on the hyperlinks provided above.

TABLE OF CONTENTS

EASA eRules.....	3
Disclaimer.....	4
Note from the editor.....	5
Incorporated amendments.....	6
Table of contents	7
Preamble	17
SUBPART A — GENERAL	24
CS 23.2000 Applicability and definitions.....	24
AMC1 23.2000 Applicability.....	24
CS 23.2005 Certification of normal-category aeroplanes	24
CS 23.2010 Accepted means of compliance	25
GM1 23.2010 Accepted means of compliance	25
GM2 23.2010 Accepted means of compliance	25
GM3 23.2010 Accepted means of compliance	28
SUBPART B — FLIGHT.....	30
CS 23.2100 Mass and centre of gravity	30
AMC1 23.2100 Mass and centre of gravity	30
AMC2 23.2100 Mass and centre of gravity	30
AMC3 23.2100 Mass and centre of gravity	30
CS 23.2105 Performance data.....	31
AMC1 23.2105 Performance data	31
AMC2 23.2105 Performance data	31
AMC3 23.2105 Performance data	32
CS 23.2110 Stall speed.....	32
AMC1 23.2110 Stall speed	32
AMC2 23.2110 Stall speed	32

AMC3 23.2110 Stall speed	32
CS 23.2115 Take-off performance.....	32
AMC1 23.2115 Take-off performance	33
AMC2 23.2115 Take-off performance	33
AMC3 23.2115 Take-off performance	33
CS 23.2120 Climb requirements.....	33
AMC1 23.2120 Climb requirements	34
AMC2 23.2120 Climb requirements	34
AMC3 23.2120 Climb requirements	34
CS 23.2125 Climb information	35
AMC1 23.2125 Climb information	35
AMC2 23.2125 Climb information	35
AMC3 23.2125 Climb information	35
CS 23.2130 Landing	35
AMC1 23.2130 Landing	36
AMC2 23.2130 Landing	36
AMC3 23.2130 Landing	36
CS 23.2135 Controllability	36
AMC1 23.2135 Controllability	37
AMC2 23.2135 Controllability	37
AMC3 23.2135 Controllability	37
CS 23.2140 Trim	37
AMC1 23.2140 Trim	38
AMC2 23.2140 Trim	38
AMC3 23.2140 Trim	38
CS 23.2145 Stability	38
AMC1 23.2145 Stability	39
AMC2 23.2145 Stability	39
AMC3 23.2145 Stability	39
CS 23.2150 Stall characteristics, stall warning, and spins	39
AMC1 23.2150 Stall characteristics, stall warning, and spins	40
AMC2 23.2150 Stall characteristics, stall warning, and spins	40

AMC3 23.2150 Stall characteristics, stall warning, and spins	40
CS 23.2155 Ground- and water-handling characteristics.....	41
AMC1 23.2155 Ground- and water-handling characteristics	41
AMC2 23.2155 Ground- and water-handling characteristics	41
AMC3 23.2155 Ground- and water-handling characteristics	41
CS 23.2160 Vibration, buffeting, and high-speed characteristics.....	41
AMC1 23.2160 Vibration, buffeting, and high-speed characteristics	42
AMC2 23.2160 Vibration, buffeting, and high-speed characteristics	42
AMC3 23.2160 Vibration, buffeting, and high-speed characteristics	42
CS 23.2165 Performance and flight characteristics requirements for flight in icing conditions	42
AMC1 23.2165 Performance and flight characteristics requirements for flight in icing conditions	43
AMC2 23.2165 Performance and flight characteristics requirements for flight in icing conditions	43
AMC3 23.2165 Performance and flight characteristics requirements for flight in icing conditions	43
FLIGHT INFORMATION	44
CS 23.2170 Operating limitations.....	44
AMC1 23.2170 Operating limitations	44
AMC2 23.2170 Operating limitations	44
AMC3 23.2170 Operating limitations	44
SUBPART C — STRUCTURES.....	45
CS 23.2200 Structural design envelope	45
AMC1 23.2200 Structural design envelope.....	45
AMC2 23.2200 Structural design envelope.....	45
AMC3 23.2200 Structural design envelope.....	46
CS 23.2205 Interaction of systems and structures	46
AMC1 23.2205 Interaction of systems and structures.....	46
AMC2 23.2205 Interaction of systems and structures.....	46
AMC3 23.2205 Interaction of systems and structures.....	47
STRUCTURAL LOADS.....	48
CS 23.2210 Structural design loads	48
AMC1 23.2210 Structural-design loads.....	48

AMC2 23.2210 Structural-design loads.....	48
AMC3 23.2210 Structural-design loads.....	49
CS 23.2215 Flight load conditions.....	49
AMC1 23.2215 Flight load conditions.....	49
AMC2 23.2215 Flight load conditions.....	50
AMC3 23.2215 Flight load conditions.....	50
CS 23.2220 Ground and water load conditions.....	50
AMC1 23.2220 Ground and water load conditions.....	50
AMC2 23.2220 Ground and water load conditions.....	51
AMC3 23.2220 Ground and water load conditions.....	51
CS 23.2225 Component loading conditions	51
AMC1 23.2225 Component loading conditions.....	52
AMC2 23.2225 Component loading conditions.....	52
AMC3 23.2225 Component loading conditions.....	53
CS 23.2230 Limit and ultimate loads	54
AMC1 23.2230 Limit and ultimate loads.....	54
AMC2 23.2230 Limit and ultimate loads.....	54
AMC3 23.2230 Limit and ultimate loads.....	54
STRUCTURAL PERFORMANCE	55
CS 23.2235 Structural strength	55
AMC1 23.2235 Structural strength.....	55
AMC2 23.2235 Structural strength.....	55
AMC3 23.2235 Structural strength.....	56
CS 23.2240 Structural durability.....	56
AMC1 23.2240 Structural durability	57
AMC2 23.2240 Structural durability	57
AMC3 23.2240 Structural durability	57
CS 23.2245 Aeroelasticity	57
AMC1 23.2245 Aeroelasticity.....	58
AMC2 23.2245 Aeroelasticity.....	58
AMC3 23.2245 Aeroelasticity.....	58
CS 23.2250 Design and construction principles.....	58
AMC1 23.2250 Design and construction principles	59
AMC2 23.2250 Design and construction principles	59
AMC3 23.2250 Design and construction principles	59
CS 23.2255 Protection of structure	60
AMC1 23.2255 Protection of structure	60
AMC2 23.2255 Protection of structure.....	61
AMC3 23.2255 Protection of structure.....	61
CS 23.2260 Materials and processes	61
AMC1 23.2260 Materials and processes.....	62
AMC2 23.2260 Materials and processes.....	62
AMC3 23.2260 Materials and processes.....	62

CS 23.2265 Special factors of safety	62
AMC1 23.2265 Special factors of safety.....	63
AMC2 23.2265 Special factors of safety.....	63
AMC3 23.2265 Special factors of safety.....	63
STRUCTURAL OCCUPANT PROTECTION	65
CS 23.2270 Emergency conditions.....	65
AMC1 23.2270 Emergency conditions	65
AMC2 23.2270 Emergency Conditions.....	66
AMC3 23.2270 Emergency Conditions.....	66
SUBPART D — DESIGN AND CONSTRUCTION	67
CS 23.2300 Flight control systems	67
AMC1 23.2300 Flight control systems	67
AMC2 23.2300 Flight control systems	67
AMC3 23.2300 Flight control systems	68
CS 23.2305 Landing gear systems	68
AMC1 23.2305 Landing gear systems	69
AMC2 23.2305 Landing gear systems	69
AMC3 23.2305 Landing gear systems	69
CS 23.2310 Buoyancy for seaplanes and amphibians	69
AMC1 23.2310 Buoyancy for seaplanes and amphibians	70
AMC2 23.2310 Buoyancy for seaplanes and amphibians	70
AMC3 23.2310 Buoyancy for seaplanes and amphibians	70
OCCUPANT SYSTEM DESIGN PROTECTION.....	71
CS 23.2315 Means of egress and emergency exits	71
AMC1 23.2315 Means of egress and emergency exits.....	71
AMC2 23.2315 Means of egress and emergency exits.....	71
AMC3 23.2315 Means of egress and emergency exits.....	72
CS 23.2320 Occupant physical environment.....	72
AMC1 23.2320 Occupant physical environment	72
AMC2 23.2320 Occupant physical environment	73
AMC3 23.2320 Occupant physical environment	73
FIRE AND HIGH ENERGY PROTECTION	74
CS 23.2325 Fire protection.....	74
AMC1 23.2325 Fire protection	74
AMC2 23.2325 Fire protection	75
AMC3 23.2325 Fire protection	75
CS 23.2330 Fire protection in designated fire zones	75

AMC1 23.2330 Fire protection in designated fire zones	75
AMC2 23.2330 Fire protection in designated fire zones	76
AMC3 23.2330 Fire protection in designated fire zones	76
CS 23.2335 Lightning protection	76
AMC1 23.2335 Lightning protection	76
AMC2 23.2335 Lightning protection	76
AMC3 23.2335 Lightning protection	77
CS 23.2340 Design and construction information	77
AMC1 23.2340 Design and construction information	77
AMC2 23.2340 Design and construction information	77
AMC3 23.2340 Design and construction information	77
SUBPART E — POWERPLANT INSTALLATION	78
CS 23.2400 Powerplant installation	78
AMC1 23.2400 Powerplant installation	78
AMC2 23.2400 Powerplant installation	79
AMC3 23.2400 Powerplant installation	80
CS 23.2405 Power or thrust control systems	81
AMC1 23.2405 Power or thrust control systems	82
AMC2 23.2405 Power or thrust control systems	82
AMC3 23.2405 Power or thrust control systems	82
CS 23.2410 Powerplant installation hazard assessment	82
AMC1 23.2410 Powerplant installation hazard assessment	83
AMC2 23.2410 Powerplant installation hazard assessment	83
AMC3 23.2410 Powerplant installation hazard assessment	84
CS 23.2415 Powerplant installation ice protection	84
AMC1 23.2415 Powerplant installation ice protection	84
AMC2 23.2415 Powerplant installation ice protection	85
AMC3 23.2415 Powerplant installation ice protection	85
CS 23.2420	85
CS 23.2425 Powerplant operational characteristics	85
AMC1 23.2425 Powerplant operational characteristics	86
AMC2 23.2425 Powerplant operational characteristics	86
AMC3 23.2425 Powerplant operational characteristics	86

CS 23.2430 Powerplant installation, energy storage and distribution systems	87
AMC1 23.2430 Powerplant installation, energy storage and distribution systems	88
AMC2 23.2430 Powerplant installation, energy storage and distribution systems	88
AMC3 23.2430 Powerplant installation, energy storage and distribution systems	89
CS 23.2435 Powerplant installation support systems.....	90
AMC1 23.2435 Powerplant installation support systems	90
AMC2 23.2435 Powerplant installation support systems	90
AMC3 23.2435 Powerplant installation support systems	91
CS 23.2440 Powerplant installation fire protection.....	91
AMC1 23.2440 Powerplant installation fire protection	91
AMC2 23.2440 Powerplant installation fire protection	92
AMC3 23.2440 Powerplant installation fire protection	92
CS 23.2445 Powerplant installation information	93
AMC1 23.2445 Powerplant installation information.....	93
AMC2 23.2445 Powerplant installation information.....	93
AMC3 23.2445 Powerplant installation information.....	93
SUBPART F — SYSTEMS AND EQUIPMENT	94
CS 23.2500 General requirements on systems and equipment function	94
AMC1 23.2500 General requirements on systems and equipment function	94
AMC2 23.2500 General requirements on systems and equipment function	95
AMC3 23.2500 General requirements on systems and equipment function	96
CS 23.2505 General requirements on equipment installation	96
AMC1 23.2505 General requirements on equipment installation	97
AMC2 23.2505 General requirements on equipment installation	97
AMC3 23.2505 General requirements on equipment installation	97
CS 23.2510 Equipment, systems, and installations.....	97
AMC1 23.2510 Equipment, systems, and installations.....	98
AMC2 23.2510 Equipment, systems, and installations.....	98

AMC3 23.2510 Equipment, systems, and installations.....	99
CS 23.2515 Electrical and electronic system lightning protection.....	99
AMC1 23.2515 Electrical and electronic system lightning protection	100
AMC2 23.2515 Electrical and electronic system lightning protection	100
AMC3 23.2515 Electrical and electronic system lightning protection	100
CS 23.2520 High-intensity radiated fields (HIRF) protection.....	100
AMC1 23.2520 High-intensity radiated fields (HIRF) protection	101
AMC2 23.2520 High-intensity radiated fields (HIRF) protection	101
AMC3 23.2520 High-intensity radiated fields (HIRF) protection	101
CS 23.2525 System power generation, storage, and distribution	101
AMC1 23.2525 System power generation, storage, and distribution.....	101
AMC2 23.2525 System power generation, storage, and distribution.....	102
AMC3 23.2525 System power generation, storage, and distribution.....	102
CS 23.2530 External and cockpit lighting	103
AMC1 23.2530 External and cockpit lighting	103
AMC2 23.2530 External and cockpit lighting	103
AMC3 23.2530 External and cockpit lighting	104
CS 23.2535 Safety equipment.....	104
AMC1 23.2535 Safety equipment.....	104
AMC2 23.2535 Safety equipment.....	104
AMC3 23.2535 Safety equipment.....	104
CS 23.2540 Flight in icing conditions.....	105
AMC1 23.2540 Flight in icing conditions.....	105
AMC2 23.2540 Flight in icing conditions.....	105
AMC3 23.2540 Flight in icing conditions.....	105
CS 23.2545 Pressurised systems elements	105
AMC1 23.2545 Pressurised systems elements	106
AMC2 23.2545 Pressurised systems elements	106
AMC3 23.2545 Pressurised systems elements	106
CS 23.2550	106

CS 23.2555 Installation of recorders (e.g. cockpit voice recorders and flight data recorders).....	106
AMC1 23.2555 Installation of recorders (e.g. cockpit voice recorders and flight data recorders).....	107
AMC2 23.2555 Installation of recorders (e.g. cockpit voice recorders and flight data recorders).....	107
AMC3 23.2555 Installation of recorders (e.g. cockpit voice recorders and flight data recorders).....	107
 SUBPART G — FLIGHT CREW INTERFACE AND OTHER INFORMATION	
.....	108
CS 23.2600 Flight crew compartment	108
AMC1 23.2600 Flight crew compartment	108
AMC2 23.2600 Flight crew compartment	109
AMC3 23.2600 Flight crew compartment	110
CS 23.2605 Installation and operation information	110
AMC1 23.2605 Installation and operation information.....	111
AMC2 23.2605 Installation and operation information.....	111
AMC3 23.2605 Installation and operation information.....	112
CS 23.2610 Instrument markings, control markings and placards	113
AMC1 23.2610 Instrument markings, control markings and placards.....	113
AMC2 23.2610 Instrument markings, control markings and placards.....	113
AMC3 23.2610 Instrument markings, control markings and placards.....	114
CS 23.2615 Flight, navigation, and powerplant instruments	115
AMC1 23.2615 Flight, navigation, and powerplant instruments.....	115
AMC2 23.2615 Flight, navigation, and powerplant instruments.....	116
AMC3 23.2615 Flight, navigation, and powerplant instruments.....	116
CS 23.2620 Aeroplane Flight Manual	116
AMC1 23.2620 Aeroplane Flight Manual	117
AMC2 23.2620 Aeroplane Flight Manual	117
AMC3 23.2620 Aeroplane Flight Manual	117

CS 23.2625 Instructions for Continued Airworthiness	118
AMC1 23.2625 Instructions for Continued Airworthiness	118
AMC2 23.2625 Instructions for Continued Airworthiness	118
AMC3 23.2625 Instructions for Continued Airworthiness	118

PREAMBLE

ED Decision 2026/003/R

CS-23 Amendment 6 and AMC & GM to CS-23 Issue 5

The following is a list of paragraphs affected by this amendment:

Subpart A	
GM1 23.2010 Accepted means of compliance	Amended
GM2 23.2010 Accepted means of compliance	Amended
GM3 23.2010 Accepted means of compliance	Amended
Subpart B	
AMC1 23.2100 Mass and centre of gravity	Amended
AMC1 23.2105 Performance data	Amended
AMC1 23.2110 Stall speed	Amended
AMC1 23.2115 Take-off performance	Amended
AMC1 23.2120 Climb requirements	Amended
AMC1 23.2125 Climb information	Amended
AMC1 23.2130 Landing	Amended
AMC1 23.2135 Controllability	Amended
AMC1 23.2140 Trim	Amended
AMC1 23.2145 Stability	Amended
AMC1 23.2150 Stall characteristics, stall warning, and spins	Amended
AMC2 23.2150 Stall characteristics, stall warning, and spins	Amended
AMC1 23.2155 Ground- and water-handling characteristics	Amended
AMC1 23.2160 Vibration, buffeting, and high-speed characteristics	Amended
AMC1 23.2165 Performance and flight characteristics requirements for flight in icing conditions	Amended
AMC1 23.2170 Operating limitations	Amended
Subpart C	
AMC1 23.2200 Structural design envelope	Amended
AMC1 23.2205 Interaction of systems and structures	Amended
AMC1 23.2210 Structural-design loads	Amended
AMC1 23.2215 Flight load conditions	Amended
AMC2 23.2215 Flight load conditions	Amended
AMC3 23.2215 Flight load conditions	Amended
AMC1 23.2220 Ground and water load conditions	Amended
AMC1 23.2225 Component loading conditions	Amended
AMC1 23.2230 Limit and ultimate loads	Amended
AMC1 23.2235 Structural strength	Amended
AMC1 23.2240 Structural durability	Amended
AMC1 23.2245 Aeroelasticity	Amended
AMC1 23.2250 Design and construction principles	Amended
AMC1 23.2255 Protection of structure	Amended

AMC1 23.2260 Materials and processes	Amended
AMC1 23.2265 Special factors of safety	Amended
AMC1 23.2270 Emergency conditions	Amended
Subpart D	
AMC1 23.2300 Flight control systems	Amended
AMC1 23.2305 Landing gear systems	Amended
AMC1 23.2310 Buoyancy for seaplanes and amphibians	Amended
AMC1 23.2315 Means of egress and emergency exits	Amended
AMC1 23.2320 Occupant physical environment	Amended
AMC1 23.2325 Fire protection	Amended
AMC1 23.2330 Fire protection in designated fire zones	Amended
AMC1 23.2335 Lightning protection	Amended
AMC1 23.2340 Design and construction information	Amended
Subpart E	
AMC1 23.2400 Powerplant installation	Amended
AMC1 23.2405 Power or thrust control systems	Amended
AMC1 23.2410 Powerplant installation hazard assessment	Amended
AMC1 23.2415 Powerplant installation ice protection	Amended
AMC1 23.2425 Powerplant operational characteristics	Amended
AMC1 23.2430 Powerplant installation, energy storage and distribution systems	Amended
AMC1 23.2435 Powerplant installation support systems	Amended
AMC1 23.2440 Powerplant installation fire protection	Amended
AMC1 23.2445 Powerplant installation information	Amended
Subpart F	
AMC1 23.2500 General requirements on systems and equipment function	Amended
GM 23.2500(b) General requirements on systems and equipment function	Removed
AMC1 23.2505 General requirements on equipment installation	Amended
AMC1 23.2510 Equipment, systems, and installations	Amended
AMC1 23.2515 Electrical and electronic system lightning protection	Amended
AMC1 23.2520 High-intensity radiated fields (HIRF) protection	Amended
AMC1 23.2525 System power generation, storage, and distribution	Amended
AMC1 23.2530 External and cockpit lighting	Amended
AMC1 23.2535 Safety equipment	Amended
AMC1 23.2540 Flight in icing conditions	Amended

AMC1 23.2545 Pressurised systems elements	Amended
AMC1 23.2555 Installation of recorders (e.g. cockpit voice recorders and flight data recorders)	Amended
Subpart G	
AMC1 23.2600 Flight crew compartment	Amended
AMC1 23.2605 Installation and operation information	Amended
AMC1 23.2610 Instrument markings, control markings and placards	Amended
AMC1 23.2615 Flight, navigation, and powerplant instruments	Amended
AMC2 23.2615 Flight, navigation, and powerplant instruments	Amended
AMC3 23.2615 Flight, navigation, and powerplant instruments	Amended
AMC1 23.2620 Aeroplane Flight Manual	Amended
AMC1 23.2625 Instructions for Continued Airworthiness	Amended

ED Decision 2023/002/R

Amendment 6

The following is a list of paragraphs affected by this amendment:

Subpart A	
GM1 23.2010	Amended (NPA 2022-103)
GM2 23.2010	Amended (NPA 2022-103)
GM3 23.2010	Created (NPA 2022-103)
Subpart B	
AMC1 23.2100	Amended (NPA 2022-103)
AMC1 23.2105	Amended (NPA 2022-103)
AMC1 23.2110	Amended (NPA 2022-103)
AMC1 23.2115	Amended (NPA 2022-103)
AMC1 23.2120	Amended (NPA 2022-103)
AMC1 23.2125	Amended (NPA 2022-103)
AMC1 23.2130	Amended (NPA 2022-103)
CS 23.2135	Amended (NPA 2022-103)
AMC1 23.2135	Amended (NPA 2022-103)
AMC1 23.2140	Amended (NPA 2022-103)
AMC1 23.2145	Amended (NPA 2022-103)
AMC1 23.2150	Amended (NPA 2022-103)
AMC2 23.2150	Amended (NPA 2022-103)
AMC1 23.2155	Amended (NPA 2022-103)
AMC1 23.2160	Amended (NPA 2022-103)
AMC1 23.2165	Amended (NPA 2022-103)
AMC2 23.2165	Amended (NPA 2022-103)
AMC1 23.2170	Amended (NPA 2022-103)
Subpart C	

AMC1 23.2200	Amended (NPA 2022-103)
AMC1 23.2205	Amended (NPA 2022-103)
AMC1 23.2210	Amended (NPA 2022-103)
AMC1 23.2215	Amended (NPA 2022-103)
AMC1 23.2220	Amended (NPA 2022-103)
AMC1 23.2225	Amended (NPA 2022-103)
AMC1 23.2230	Amended (NPA 2022-103)
AMC1 23.2235	Amended (NPA 2022-103)
AMC1 23.2240	Amended (NPA 2022-103)
AMC1 23.2250	Amended (NPA 2022-103)
AMC1 23.2255	Amended (NPA 2022-103)
AMC1 23.2260	Amended (NPA 2022-103)
AMC1 23.2265	Amended (NPA 2022-103)
AMC1 23.2270	Amended (NPA 2022-103)
Subpart D	
AMC1 23.2300	Amended (NPA 2022-103)
AMC1 23.2305	Amended (NPA 2022-103)
AMC1 23.2310	Amended (NPA 2022-103)
AMC1 23.2315	Amended (NPA 2022-103)
AMC1 23.2320	Amended (NPA 2022-103)
AMC1 23.2325	Amended (NPA 2022-103)
AMC1 23.2330	Amended (NPA 2022-103)
AMC1 23.2335	Amended (NPA 2022-103)
AMC1 23.2340	Amended (NPA 2022-103)
Subpart E	
AMC1 23.2400	Amended (NPA 2022-103)
AMC1 23.2405	Amended (NPA 2022-103)
AMC1 23.2410	Amended (NPA 2022-103)
AMC1 23.2415	Amended (NPA 2022-103)
AMC2 23.2415	Amended (NPA 2022-103)
AMC1 23.2425	Amended (NPA 2022-103)
CS 23.2430	Amended (NPA 2022-103)
AMC1 23.2430	Amended (NPA 2022-103)
AMC1 23.2435	Amended (NPA 2022-103)
AMC1 23.2440	Amended (NPA 2022-103)
AMC1 23.2445	Amended (NPA 2022-103)
Subpart F	
AMC1 23.2500	Amended (NPA 2022-103)
AMC1 23.2505	Amended (NPA 2022-103)
AMC1 23.2510	Amended (NPA 2022-103)
CS 23.2515	Amended (NPA 2022-103)
AMC1 23.2515	Amended (NPA 2022-103)
AMC1 23.2520	Amended (NPA 2022-103)
AMC1 23.2525	Amended (NPA 2022-103)
AMC2 23.2525	Amended (NPA 2022-103)
AMC3 23.2525	Amended (NPA 2022-103)

AMC1 23.2530	Amended (NPA 2022-103)
AMC1 23.2535	Amended (NPA 2022-103)
AMC1 23.2540	Amended (NPA 2022-103)
AMC2 23.2540	Amended (NPA 2022-103)
AMC1 23.2545	Amended (NPA 2022-103)
AMC1 23.2555	Amended (NPA 2022-103)
Subpart G	
AMC1 23.2600	Amended (NPA 2022-103)
AMC1 23.2605	Amended (NPA 2022-103)
AMC1 23.2610	Amended (NPA 2022-103)
AMC1 23.2615	Amended (NPA 2022-103)
AMC2 23.2615	Amended (NPA 2022-103)
AMC3 23.2615	Amended (NPA 2022-103)
AMC1 23.2620	Amended (NPA 2022-103)
AMC1 23.2625	Amended (NPA 2022-103)

ED Decision 2017/013/R

Amendment 5

The following is a list of paragraphs affected by this amendment:

Subpart A	
CS 23.1 through CS 23.3	Deleted and moved to AMC (NPA 2016-05)
CS 23.2000 through CS 23.2010	Created (NPA 2016-05)
Subpart B	
CS 23.21 through CS 23.253	Deleted and moved to AMC (NPA 2016-05)
CS 23.2100 through CS 23.2170	Created (NPA 2016-05)
Subpart C	
CS 23.301 through CS 23.575	Deleted and moved to AMC (NPA 2016-05)
CS 23.2200 through CS 23.2270	Created (NPA 2016-05)
AMC — Subpart C	Deleted and moved to AMC (NPA 2016-05)
Subpart D	
CS 23.601 through CS 23.871	Deleted and moved to AMC (NPA 2016-05)
CS 23.2300 through CS 23.2340	Created (NPA 2016-05)
AMC — Subpart D	Deleted and moved to AMC (NPA 2016-05)
Subpart E	
CS 23.901 through CS 23.1203	Deleted and moved to AMC (NPA 2016-05)
CS 23.2400 through CS 23.2445	Created (NPA 2016-05)
AMC — Subpart E	Deleted and moved to AMC (NPA 2016-05)
Subpart F	
CS 23.1301 through CS 23.1461	Deleted and moved to AMC (NPA 2016-05)
CS 23.2500 through CS 23.2555	Created (NPA 2016-05)
AMC — Subpart F	Deleted and moved to AMC (NPA 2016-05)
Subpart G	
CS 23.1501 through CS 23.1589	Deleted and moved to AMC (NPA 2016-05)

CS 23.2600 through CS 23.2625	Created (NPA 2016-05)
AMC — Subpart G	Deleted and moved to AMC (NPA 2016-05)
Appendices	
Appendix A through K	Deleted and moved to AMC (NPA 2016-05)
AMC — Appendix A	Deleted and moved to AMC (NPA 2016-05)
Flight Test Guide (FTG)	Deleted and moved to AMC (NPA 2016-05)

ED Decision 2015/018/R

Amendment 4

The following is a list of paragraphs affected by this amendment:

Subpart F	
CS 23.1306	Created (NPA 2014-16)
CS 23.1308	Created (NPA 2014-16)
Appendix K	Created (NPA 2014-16)
CS 23.1309	Amended (NPA 2014-16)

ED Decision 2012/012/R

Amendment 3

The following is a list of paragraphs affected by this amendment:

Subpart D	
CS 23.851	Amended (NPA 2011-14)
AMC 23.851(c)	Amended (NPA 2011-14)
Subpart E	
CS 23.1197	Amended (NPA 2011-14)
AMC 23.1197	Created (NPA 2011-14)

ED Decision 2010/008/R

Amendment 2

The following is a list of paragraphs affected by this amendment:

Subpart B	
CS 23.221	Amended (Editorial correction)
Subpart C	
Appendix D	Amended (Editorial correction)
AMC 23.573(a)(1)&(3)	Amended (NPA 2009-06)
Subpart D	
CS 23.603	Amended (NPA 2009-06)
AMC 23.603	Deleted (NPA 2009-06)
AMC 23.613	Amended (NPA 2009-06)
AMC 23.629	Amended (NPA 2009-06 & Editorial correction)
CS 23.813(b)(4)	Amended (Editorial correction)
Subpart E	
CS 23.909	Amended (Editorial correction)
Flight Test Guide (FTG)	

192 Paragraph 23.909	Amended (Editorial correction)
207 Paragraph 23.959	Amended (Editorial correction)
208 Paragraph 23.961	Amended (Editorial correction)
307 Paragraph 23.1329	Amended (Editorial correction)

ED Decision 2009/001/R

Amendment 1

The following is a list of paragraphs affected by this amendment:

Preamble	Preamble added
Subpart B	
CS 23.49(c)	Amended (NPA 2008-08)
CS 23.49(d)	Created (NPA 2008-08)
Subpart C	
CS 23.562(d)	Created (NPA 2008-08)
CS 23.562(e)	Amended (NPA 2008-08)

SUBPART A — GENERAL

CS 23.2000 Applicability and definitions

ED Decision 2017/013/R

- (a) This Certification Specification prescribes airworthiness standards for the issuance of type certificates, and changes to those certificates, for aeroplanes in the normal category.
- (b) For the purposes of this Certification Specification, the following definition applies:
'Continued safe flight and landing' means an aeroplane is capable of continued controlled flight and landing, possibly using emergency procedures, without requiring exceptional pilot skill or strength. Upon landing, some aeroplane damage may occur as a result of a failure condition.

AMC1 23.2000 Applicability

ED Decision 2017/025/R

The applicability of the acceptable means of compliance (AMC) is limited to the scope of CS-23 (Amendment 5 and later). The applicability of the individual AMC that are provided in Subpart B through G can be restricted to a specific type of design, type of operation or any other criterion. The applicability of each AMC is therefore specified within that AMC. Demonstration of compliance using a published AMC outside of that applicability does not provide for presumption of compliance with the related requirement.

CS 23.2005 Certification of normal-category aeroplanes

ED Decision 2017/013/R

- (a) Certification in the normal category applies to aeroplanes with a passenger seating configuration of 19 or less and a maximum certified take-off mass of 8 618 kg (19 000 pounds) or less.
- (b) Aeroplane certification levels are:
 - (1) Level 1 — for aeroplanes with a maximum seating configuration of 0 to 1 passengers;
 - (2) Level 2 — for aeroplanes with a maximum seating configuration of 2 to 6 passengers;
 - (3) Level 3 — for aeroplanes with a maximum seating configuration of 7 to 9 passengers; and
 - (4) Level 4 — for aeroplanes with a maximum seating configuration of 10 to 19 passengers.
- (c) Aeroplane performance levels are:
 - (1) Low speed — for aeroplanes with a V_{NO} or $V_{MO} \leq 250$ knots calibrated airspeed (KCAS) or a $M^{MO} \leq 0.6$; and
 - (2) High speed — for aeroplanes with a V_{NO} or $V_{MO} > 250$ KCAS or an $M_{MO} > 0.6$.
- (d) Aeroplanes not certified for aerobatics may be used to perform any manoeuvre incident to normal flying, including:
 - (1) stalls (except whip stalls); and
 - (2) lazy eights, chandelles, and steep turns, in which the angle of bank is not more than 60 degrees.

- (e) Aeroplanes certified for aerobatics may be used to perform manoeuvres without limitations, other than those limitations established under Subpart G.

CS 23.2010 Accepted means of compliance

ED Decision 2017/013/R

- (a) An applicant must comply with this CS using an acceptable means of compliance (AMC) issued by EASA, or another means of compliance which may include consensus standards, when specifically accepted by EASA.
- (b) An applicant requesting EASA to accept a means of compliance must provide the means of compliance to EASA in an acceptable form and manner.

GM1 23.2010 Accepted means of compliance

ED Decision 2026/003/R

For compliance demonstration, applicants will use the issue of the AMC & GM which is current on the date of application, as reflected in the certification programme for the certification basis determined by EASA.

This current issue, however, does not automatically invalidate the previous and later issues of the AMC & GM to CS-23, unless this is specifically identified as such in the AMC & GM. Applicants can, therefore, agree with EASA in the certification programme to use such previous issues of the AMC & GM to demonstrate compliance with the certification basis.

Whenever an earlier AMC is no longer considered to be acceptable for the demonstration of compliance, the restrictions on its use will be stated in a remark on the specific line of that CS and the related AMC. In particular, AMC2&3 to CS-23/CS-VLA Subpart B to Subpart G (which reflect respectively CS-23 Amendment 4 and CS-VLA Amendment 1) will not be updated to cover new technologies or methods. However, they are still accepted as means of compliance. EASA will restrict their use in the AMC only when they no longer appropriately address new safety concerns or the associated safety levels.

[AMC & GM to CS-23: Issue 3]

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

GM2 23.2010 Accepted means of compliance

ED Decision 2026/003/R

The AMC to certification specifications (CS) for Normal-Category Aeroplanes (CS-23 Amendment 5 and later) illustrate means, but not the only means, by which a requirement contained in CS-23 can be met. Satisfactory demonstration of compliance using the AMC shall provide for presumption of compliance with the related requirement. The AMC are a way to facilitate certification tasks for the applicant and the competent authority. Due to changes in technology or application of technology in a way that has not been considered or not (yet) included in the AMC, the appropriate application of this AMC in the certification of a design requires a review by the authority.

CS-23 Amendment 5 and later maintains the existing level of safety of CS-23 Amendment 4 and CS-VLA Amendment 1, except for areas addressing loss of control and icing, for which the safety level was increased. Achieving this level of safety through compliance with CS-23 Amendment 5 and later for a

given certification project may require the use of additional means of compliance beyond those provided in this AMC, depending on the details of the specific design.

Applicants may propose designs with novel or unusual features for which neither AMC1 nor the EASA Certification Specifications (CS-23 Amendment 4 and CS-VLA Amendment 1) contain appropriate AMC for showing compliance with CS-23 Amendment 5 and later. Therefore, applicants proposing the use of this AMC to CS-23 as a means of complying with CS-23 Amendment 5 and later for aeroplanes with novel or unusual design features may need to gain acceptance of additional means of compliance under [CS 23.2010](#).

AMC1 CS-23 Subpart B through Subpart G contains means of compliance that consist of a listing of consensus standards at their specific revisions that have been reviewed by EASA and accepted as AMC to CS-23. The scope and content of the referenced consensus standard can, however, differ from the overall scope of CS-23 or the objectives of the requirement. Therefore, using such a referenced consensus standard requires the applicant to identify what is applicable within that consensus standard and to seek agreement with the authority for agreement of the selected consensus standard and applied paragraphs. This is the so-called building-block flexibility that is built into CS-23.

Applicable revision of ASTM F3264

For the purpose of AMC1 to CS-23, EASA has assessed and accepted the most recent available revision of ASTM F3264, currently **ASTM F3264-24**.

Where more recent revisions of individual consensus standards were available at the time of assessment, EASA also considered them with the aim of closing existing remarks in AMC1. As a result, some standards listed in AMC1 may refer to a revision that differs from the one included in **ASTM F3264-24**. It is expected that these revisions will be incorporated into a future update of **ASTM F3264**.

Deviations from consensus standards

Where EASA determines that a deviation from a referenced consensus standard is necessary to achieve the level of safety required by the respective CS-23 Amendment, this is indicated by a corresponding remark in AMC1.

AMC2 CS-23 Subpart B through Subpart G contains means of compliance that refer to the previous Amendment 4 of CS-23. These AMC are included for the (administrative) convenience of both the applicant and EASA when using an existing certification basis. AMC2 in Sections B through G identify which CS-23 Amendment 4 requirements contain an accepted demonstration of compliance with the requirement. This AMC2 CS-23 Subpart B through Subpart G is applicable for fixed wing aeroplanes with a passenger-seating configuration of 19 or less and a maximum certificated take-off mass of 8 618 kg (19 000 pounds) or less.

Before the entry into force of Amendment 5 of CS-23, CS-23 was included in the certification basis that often required complementing special conditions (refer to point 21.A.16B of Part 21¹) when the certification specification did not contain adequate or appropriate safety standards for the product. These special conditions can be applied to complement AMC2 when required.

AMC3 CS-23 Subpart B through Subpart G contains means of compliance that refer to the previous Amendment 1 of CS-VLA. These AMC are included for the (administrative) convenience of both the applicant and EASA when using an existing certification basis. AMC3 that are provided in Sections B through G identify which CS-VLA Amendment 1 requirement(s) contain an accepted demonstration of compliance with the requirement. This AMC3 CS-23 Subpart B through Subpart G is applicable to

¹ Regulation (EU) No 748/2012 of 3 August 2012 laying down implementing rules for the airworthiness and environmental certification of aircraft and related products, parts and appliances, as well as for the certification of design and production organisations (OJ L 224, 21.8.2012, p. 1). <http://eur-lex.europa.eu/legal-content/EN/TXT/?qid=1473415871666&uri=CELEX:32012R0748>

aeroplanes with a single engine (spark- or compression-ignition) having not more than two seats, with a maximum certificated take-off weight of not more than 750 kg and a stalling speed in the landing configuration of not more than 83 km/h (45 knots)(CAS), to be approved for day VFR only. This AMC3 is applicable for non-aerobatic operations including:

- any manoeuvre incident to normal flying;
- stalls (except whip stalls); and
- lazy eights, chandelles, and steep turns, in which the angle of bank is not more than 60°.

Before the entry into force of Amendment 5 of CS-23, CS-VLA was included in the certification basis that often required complementing special conditions (refer to point 21.A.16B in Part 21) when the certification specification did not contain adequate or appropriate safety standards for the product. These special conditions can be applied to complement AMC3 when required.

Availability of referenced consensus standards

The referenced consensus standard documents are available from their issuing standards body:

- ASTM documents may be purchased from:

ASTM International
100 Barr Harbor Drive, PO Box C700
West Conshohocken, Pennsylvania
19428-2959, USA
(Website: www.astm.org)

[AMC & GM to CS-23: Issue 3]
[AMC & GM to CS-23: Issue 4]
[AMC & GM to CS-23: Issue 5]

GM3 23.2010 Accepted means of compliance

ED Decision 2026/003/R

The following table provides an overview of the ASTM International Technical Committee F44 (hereinafter ‘ASTM F44’) consensus standards that are included in AMC1 as an acceptable means of compliance with CS-23. It also gives the revision number of the ASTM consensus standards as changed between Issue 4 and Issue 5 of AMC1 to CS 23.

	AMC & GM to CS-23 Issue 5 (ED Decision 2026/003/R)	AMC & GM to CS-23 Issue 4 (ED Decision 2023/002/R, ED Decision 2025/019/R*)
ASTM consensus standard number and title	ASTM consensus standard revision	ASTM consensus standard revision
F2490 Standard Guide for Aircraft Electrical Load and Power Source Capacity Analysis	20	20
F3061/F3061M Standard Specification for Systems and Equipment in Small Aircraft	24a	20
F3062/F3062M Standard Specification for Aircraft Powerplant Installation	20	20
F3063/F3063M Standard Specification for Aircraft Fuel Storage and Delivery	21	20
F3064/F3064M Standard Specification for Aircraft Powerplant Control, Operation, and Indication	21	21
F3065/F3065M Standard Specification for Aircraft Propeller System Installation	21a	21a
F3066/F3066M Standard Specification for Aircraft Powerplant Installation Hazard Mitigation	18	18
F3082/F3082M Standard Specification for Weights and Centers of Gravity of Aircraft	22	17
F3083/F3083M Standard Specification for Emergency Conditions, Occupant Safety and Accommodations	20a	20a
F3093/F3093M Standard Specification for Aeroelasticity Requirements	21	21
F3114 Standard Specification for Structures	21	21
F3115/F3115M Standard Specification for Structural Durability for Small Aeroplanes	15	15*
F3116/F3116M Standard Specification for Design Loads and Conditions	24	18e2
F3117/F3117M Standard Specification for Crew Interface in Aircraft	24a	20
F3120/F3120M Standard Specification for Ice Protection for General Aviation Aircraft	20	20
F3173/F3173M Standard Specification for Aircraft Handling Characteristics	21a	21
F3174/F3174M Standard Specification for Establishing Operating Limitations and Information for Aeroplanes	21	19

F3179/F3179M Standard Specification for Performance of Aircraft	22e1	20
F3180/F3180M Standard Specification for Low-Speed Flight Characteristics of Aircraft	25	21
F3227/F3227M Standard Specification for Environmental Systems in Aircraft	25	21
F3228 Standard Specification for Flight Data and Voice Recording in Small Aircraft	21	17
F3229/F3229M Standard Practice for Static Pressure System Tests in Small Aircraft	23a	17
F3230 Standard Practice for Safety Assessment of Systems and Equipment in Small Aircraft	25	20a
F3231/F3231M Standard Specification for Electrical Systems for Aircraft with Combustion Engine Electrical Power Generation	24	21
F3232/F3232M Standard Specification for Flight Controls in Small Aircraft	25	20
F3233/F3233M Standard Specification for Flight and Navigation Instrumentation in Aircraft	23b	21
F3234/F3234M Standard Specification for Exterior Lighting in Small Aircraft	21	17
F3235 Standard Specification for Aircraft Storage Batteries	22	17a
F3236 Standard Specification for High Intensity Radiated Field (HIRF) Protection in Small Aircraft	21a	17
F3254 Standard Specification for Aircraft Interaction of Systems and Structures	22	19
F3309/F3309M Standard Practice for Simplified Safety Assessment of Systems and Equipment in Small Aircraft	24a	21
F3331 Standard Practice for Aircraft Water Loads	18	18
F3367 Standard Practice for Simplified Methods for Addressing High Intensity Radiated Fields (HIRF) and Indirect Effects of Lightning on Aircraft	23	/
F3380 Standard Practice for Structural Compliance of Very Light Aeroplanes	19	19
F3396/F3396M Standard Practice for Aircraft Simplified Loads Criteria	20	20
F3397/F3397M Standard Practice for Aeroplane Turbine Fuel System Hot Weather Operations	21	/
F3408/F3408M Standard Specification for Aircraft Emergency Parachute Recovery Systems	21	21
F3432 Standard Practice for Powerplant Instruments	20a	20a
F3498 Standard Practice for Developing Simplified Fatigue Load Spectra	21	/
F3532 Standard Practice for Protection of Aircraft Systems from Intentional Unauthorized Electronic Interactions	25	/

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

SUBPART B — FLIGHT

CS 23.2100 Mass and centre of gravity

ED Decision 2017/013/R

- (a) The applicant must determine limits for mass and centre of gravity that provide for the safe operation of the aeroplane.
- (b) The applicant's design must comply with each requirement of this Subpart at critical combinations of mass and centre of gravity within the aeroplane's range of loading conditions using acceptable tolerances.
- (c) The condition of the aeroplane at the time of determining its empty mass and centre of gravity must be well defined and easily repeatable.

AMC1 23.2100 Mass and centre of gravity

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.1 Weight/Mass and Centre of Gravity

5.1.1 [F3082/F3082M-22](#) Standard Specification for Weights and Centers of Gravity of Aircraft

5.1.2 [F3114-21](#) Standard Specification for Structures

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2100 Mass and centre of gravity

ED Decision 2017/025/R

CS-23 Amdt 4

23.21 Proof of compliance

23.23 Load distribution limits

23.25 Weight limits

23.29 Empty weight and corresponding center of gravity

23.31 Removable ballast

23.871 Levelling means

AMC3 23.2100 Mass and centre of gravity

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.21 Proof of compliance

VLA.23 Load distribution limits

VLA.25 Weight limits

VLA.29 Empty weight and corresponding center of gravity

VLA.871 Levelling means

CS 23.2105 Performance data

ED Decision 2017/013/R

- (a) Unless otherwise prescribed, an aeroplane must meet the performance requirements of this Subpart in:
 - (1) still air and standard atmospheric conditions at sea level for all aeroplanes; and
 - (2) ambient atmospheric conditions within the operating envelope for:
 - (i) Level-1 high-speed and Level-2 high-speed aeroplanes; and
 - (ii) Level-3 and Level-4 aeroplanes.
- (b) Unless otherwise prescribed, the applicant must develop the performance data required by this Subpart for the following conditions:
 - (1) airport altitudes from sea level to 3 048 m (10 000 ft); and
 - (2) temperatures above and below standard day temperature that are within the range of operating limitations if those temperatures could have a negative effect on performance.
- (c) The procedures used for determining take-off and landing distances must be executable consistently by pilots of average skill in atmospheric conditions expected to be encountered in service.
- (d) Performance data determined in accordance with CS 23.2105(b) must account for losses due to atmospheric conditions, cooling needs, and other demands on power sources.

AMC1 23.2105 Performance data

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.2 Performance Data

[F3179/F3179M-22e1](#) Standard Specification for Performance of Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2105 Performance data

ED Decision 2017/025/R

CS-23 Amdt 4

23.45 Performance – General

AMC3 23.2105 Performance data

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.45 Performance - General

CS 23.2110 Stall speed

ED Decision 2017/013/R

The applicant must determine the aeroplane stall speed or the minimum steady flight speed for each flight configuration used in normal operations, including take-off, climb, cruise, descent, approach, and landing. The stall speed or minimum steady flight speed determination must account for the most adverse conditions for each flight configuration.

AMC1 23.2110 Stall speed

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.3 Stall Speed

[F3179/F3179M-22e1](#) Standard Specification for Performance of Aircraft

Remarks

For stall speed, use no later revision than F3179-22e1.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2110 Stall speed

ED Decision 2017/025/R

CS-23 Amdt 4

23.49 Stalling speed

AMC3 23.2110 Stall speed

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.49 Stalling speed

CS 23.2115 Take-off performance

ED Decision 2017/013/R

- (a) The applicant must determine aeroplane take-off performance accounting for:
- (1) stall speed safety margins;
 - (2) minimum control speeds; and
 - (3) climb gradients.

- (b) For single-engine aeroplanes and Levels 1, 2, and 3 low-speed multi-engine aeroplanes, take-off performance includes the determination of ground roll and initial climb distance to 15 m (50 ft) above the take-off surface.
- (c) For high-speed multi-engine aeroplanes of Levels 1, 2, and 3, and for all Level-4 multi-engine aeroplanes, take-off performance includes a determination of the following distances after a sudden critical loss of thrust:
 - (1) an aborted take-off at critical speed;
 - (2) ground roll and initial climb to 11 m (35 ft) above the take-off surface; and
 - (3) net take-off flight path.

AMC1 23.2115 Take-off performance

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.4 Take-off Performance

[F3179/F3179M-22e1](#) Standard Specification for Performance of Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2115 Take-off performance

ED Decision 2017/025/R

CS-23 Amdt 4

23.51 Takeoff speeds

23.53 Takeoff performance

23.55 Accelerate-stop distance

23.57 Takeoff path

23.59 Takeoff distance and takeoff run

23.61 Takeoff flight path

AMC3 23.2115 Take-off performance

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.51 Takeoff speeds

CS 23.2120 Climb requirements

ED Decision 2017/013/R

The design must comply with the following minimum climb performance out of ground effect:

- (a) with all engines operating and in the initial climb configuration(s):
 - (1) for Level-1 and -2 low-speed aeroplanes, a climb gradient of 8.3 % for landplanes and 6.7 % for seaplanes and amphibians; and

- (2) for Level-1 and -2 high-speed aeroplanes and all Level-3 and -4 aeroplanes, a climb gradient at take-off of 4 %.
- (b) after a critical loss of thrust on multi-engine aeroplanes:
 - (1) for Level-1 and -2 low-speed aeroplanes that do not meet single-engine crashworthiness requirements, a climb gradient of 1.5 % at a pressure altitude of 1 524 m (5 000 ft) in the cruise configuration;
 - (2) for Level-1 and -2 high-speed aeroplanes, and Level-3 low-speed aeroplanes, a 1 % climb gradient at 122 m (400 ft) above the take-off surface with the landing gear retracted and flaps in the take-off configuration; and
 - (3) for Level-3 high-speed aeroplanes and all Level-4 aeroplanes, a 2 % climb gradient at 122 m (400 ft) above the take-off surface with the landing gear retracted and flaps in the approach configuration;
- (c) a climb gradient of 3 % during balked landing, without creating undue pilot workload, with the landing gear extended and flaps in the landing configuration(s).

AMC1 23.2120 Climb requirements

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.5 Climb Requirements

[F3179/F3179M-22e1](#) Standard Specification for Performance of Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2120 Climb requirements

ED Decision 2017/025/R

CS-23 Amdt 4

23.63 Climb: General

23.65 Climb: All engines operating

AMC3 23.2120 Climb requirements

ED Decision 2023/002/R

CS-VLA Amdt 1

CS-VLA 65 'Climbs': All engines operating

Remarks

To demonstrate compliance with [CS 23.2120](#), the climb gradient should be determined, using [F3179M 20](#) 'Standard Specification for Performance of Aircraft'.

CS 23.2125 Climb information

ED Decision 2017/013/R

- (a) The applicant must determine, as applicable, climb and/or descent performance:
- (1) for all engines operating;
 - (2) following a critical loss of thrust on take-off; and
 - (3) after a critical loss of thrust, during the en route phase of flight.

AMC1 23.2125 Climb information

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.6 Climb Information

[F3179/F3179M-22e1](#) Standard Specification for Performance of Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2125 Climb information

ED Decision 2017/025/R

CS-23 Amdt 4

23.66 Takeoff climb: one engine inoperative

23.67 Climb: One engine inoperative

23.69 En route climb/descent

23.71 Glide: single engine airplanes

AMC3 23.2125 Climb information

ED Decision 2017/025/R

None

CS 23.2130 Landing

ED Decision 2017/013/R

The applicant must determine the following, for standard temperatures at critical combinations of mass and altitude within the operational limits:

- (a) the distance, starting from a height of 15 m (50 ft) above the landing surface, required to land and come to a stop; and
- (b) the approach and landing speeds, configurations, and procedures, which allow a pilot of average skill to land within the published landing distance consistently and without causing damage or injury, and which allow for a safe transition to the balked-landing conditions.

AMC1 23.2130 Landing

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.7 Landing

[F3179/F3179M-22e1](#) Standard Specification for Performance of Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2130 Landing

ED Decision 2017/025/R

CS-23 Amdt 4

23.73 Reference landing approach speed

23.75 Landing distance

23.77 Balked landing

AMC3 23.2130 Landing

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.75 Landing distance

VLA.77 Balked landing

CS 23.2135 Controllability

ED Decision 2023/002/R

- (a) The aeroplane must be controllable and manoeuvrable, without requiring exceptional piloting skills, alertness, or strength, within the operating envelope:
 - (1) at all loading conditions for which certification is requested;
 - (2) during all phases of flight;
 - (3) with likely reversible flight control or propulsion system failure; and
 - (4) during configuration changes.
- (b) The aeroplane must be able to make a safe landing, using the steepest approved approach gradient procedures and providing a reasonable safe margin below V_{REF} or above the approach angle of attack.
- (c) V_{MC} is the calibrated airspeed at which, following the sudden critical loss of thrust, it is possible to maintain control of the aeroplane. For multi-engine aeroplanes, the applicant must determine V_{MC} , if applicable, for the most critical configurations used in take-off and landing operations.
- (d) If the applicant requests certification of an aeroplane for aerobatics, the applicant must demonstrate those aerobatic manoeuvres for which certification is requested and determine entry speeds.

AMC1 23.2135 Controllability

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.8 Controllability

[F3173/F3173M-21a](#) Standard Specification for Aircraft Handling Characteristics

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2135 Controllability

ED Decision 2017/025/R

CS-23 Amdt 4

23.141 Flight Characteristics -General

23.143 Controllability and Manoeuvrability - General

23.145 Longitudinal control

23.147 Directional and lateral control

23.149 Minimum control speed

23.151 Acrobatic manoeuvres

23.153 Control during landings

23.155 Elevator control force in manoeuvres

23.157 Rate of roll

AMC3 23.2135 Controllability

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.141 Flight Characteristics -General

VLA.143 Controllability and Manoeuvrability - General

VLA.145 Longitudinal control

VLA.153 Control during landings

VLA.155 Elevator control force in manoeuvres

VLA.157 Rate of roll

CS 23.2140 Trim

ED Decision 2017/013/R

(a) The aeroplane must maintain lateral and directional trim without further force upon, or movement of, the primary flight controls or corresponding trim controls by the pilot, or the flight control system, under the following conditions:

- (1) for Level-1, -2, and -3 aeroplanes, in cruise;
- (2) for Level-4 aeroplanes, in normal operations.

- (b) The aeroplane must maintain longitudinal trim without further force upon, or movement of, the primary flight controls or corresponding trim controls by the pilot, or the flight control system, under the following conditions:
- (1) climb,
 - (2) level flight,
 - (3) descent,
 - (4) approach.
- (c) Residual control forces must not fatigue or distract the pilot during normal operations of the aeroplane and likely abnormal or emergency operations, including a critical loss of thrust on multi-engine aeroplanes.

AMC1 23.2140 Trim

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.9 Trim

[F3173/F3173M-21a](#) Standard Specification for Aircraft Handling Characteristics

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2140 Trim

ED Decision 2017/025/R

CS-23 Amdt 4

23.161 Trim

AMC3 23.2140 Trim

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.161 Trim

CS 23.2145 Stability

ED Decision 2017/013/R

- (a) Aeroplanes not certified for aerobatics must:
- (1) have static longitudinal, lateral, and directional stability in normal operations;
 - (2) have dynamic short period and Dutch roll stability in normal operations; and
 - (3) provide stable control feedback throughout the operating envelope.
- (b) No aeroplane may exhibit any divergent longitudinal stability characteristic so unstable as to increase the pilot's workload or otherwise endanger the aeroplane and its occupants.

AMC1 23.2145 Stability

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.10 Stability

[F3173/F3173M-21a](#) Standard Specification for Aircraft Handling Characteristics

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2145 Stability

ED Decision 2017/025/R

CS-23 Amdt 4

23.171 Stability – General

23.173 Static longitudinal stability

23.175 Demonstration of static longitudinal stability

23.177 Static directional and lateral stability

23.181 Dynamic stability

AMC3 23.2145 Stability

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.171 Stability – General

VLA.173 Static longitudinal stability

VLA.175 Demonstration of static longitudinal stability

VLA.177 Static directional and lateral stability

VLA.181 Dynamic stability

CS 23.2150 Stall characteristics, stall warning, and spins

ED Decision 2017/013/R

- (a) The aeroplane must have controllable stall characteristics in straight flight, turning flight, and accelerated turning flight with a clear and distinctive stall warning that provides sufficient margin to prevent inadvertent stalling. A stall warning that is mutable for aerobatic flight phases is acceptable.
- (b) Single-engine aeroplanes, not certified for aerobatics, must not have a tendency to hazardously depart from controlled flight inadvertently.
- (c) Level-1 and -2 multi-engine aeroplanes, not certified for aerobatics, must not have a tendency to hazardously depart controlled flight inadvertently from thrust asymmetry after a critical loss of thrust.
- (d) Aeroplanes certified for aerobatics that include spins must have controllable stall characteristics and the ability to recover within one and one-half additional turns after initiation of the first control action from any point in a spin, not exceeding six turns or any greater number of turns

for which certification is requested, while remaining within the operating limitations of the aeroplane.

- (e) Aeroplanes intended for aerobatics have the ability to recover from any approved manoeuvre, without exceeding limitations or exhibiting unsafe characteristics.

AMC1 23.2150 Stall characteristics, stall warning, and spins

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.11 Stall Characteristics, Stall Warning, and Spins

[F3180/F3180M-25](#) Standard Specification for Low-Speed Flight Characteristics of Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2150 Stall characteristics, stall warning, and spins

ED Decision 2026/003/R

CS-23 Amdt 4

23.201 Wings level stall

23.203 Turning Flight and accelerated turning stalls

23.207 Stall Warning

23.221 Spinning

Remarks

[CS 23.2150](#)(b) and (c) are not covered by this AMC2. Applicants may use the provision in ASTM F3180-25 to show compliance with [CS 23.2150](#).

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC3 23.2150 Stall characteristics, stall warning, and spins

ED Decision 2019/020/R

CS VLA Amdt 1

VLA.201 Wings level stall

VLA.203 Turning Flight and accelerated turning stalls

VLA.207 Stall Warning

VLA.221 Spinning

Remarks

VLA.221(a) is not accepted as AMC to [23.2150](#) only VLA.221(b) can be used.

CS 23.2155 Ground- and water-handling characteristics

ED Decision 2017/013/R

- (a) The aeroplane has controllable longitudinal and directional handling characteristics during taxi, take-off, and landing for the anticipated operation.

AMC1 23.2155 Ground- and water-handling characteristics

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.12 Ground and Water Handling Characteristics

[F3173/F3173M-21a](#) Standard Specification for Aircraft Handling Characteristics

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2155 Ground- and water-handling characteristics

ED Decision 2017/025/R

CS-23 Amdt 4

23.231 Longitudinal stability and control

23.233 Directional stability and control

23.235 Operation on unpaved surfaces

23.237 Operation on water

23.239 Spray characteristics

AMC3 23.2155 Ground- and water-handling characteristics

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.231 Longitudinal stability and control

VLA.233 Directional stability and control

VLA.235 Operation on unpaved surfaces

VLA.239 Spray characteristics

CS 23.2160 Vibration, buffeting, and high-speed characteristics

ED Decision 2017/013/R

- (a) Vibration and buffeting, for operations up to V_D/M_D , must not interfere with the control of the aeroplane or cause excessive fatigue to the flight crew. Stall warning buffet within these limits is allowable.
- (b) For high-speed aeroplanes and all aeroplanes with a maximum operating altitude greater than 7 625 m (25 000 ft) pressure altitude, there must be no perceptible buffeting in cruise configuration at 1 g and at any speed up to V_{MO}/M_{MO} , except stall buffeting.
- (c) For high-speed aeroplanes, the applicant must determine the positive manoeuvring load factors at which the onset of perceptible buffet occurs in the cruise configuration within the operational

envelope. Likely inadvertent excursions beyond this boundary must not result in structural damage.

- (d) High-speed aeroplanes must have recovery characteristics that do not result in structural damage or loss of control, beginning at any likely speed up to V_{MO}/M_{MO} , following:
- (1) an inadvertent speed increase; and
 - (2) a high-speed trim upset for aeroplanes where dynamic pressure can impair the longitudinal trim system operation.

AMC1 23.2160 Vibration, buffeting, and high-speed characteristics

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.13 Vibration, Buffeting, and High-Speed Characteristics

[F3173/F3173M-21a](#) Standard Specification for Aircraft Handling Characteristics

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2160 Vibration, buffeting, and high-speed characteristics

ED Decision 2017/025/R

CS-23 Amdt 4

23.251 Vibration and buffeting

23.253 High-speed characteristics

AMC3 23.2160 Vibration, buffeting, and high-speed characteristics

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.251 Vibration and buffeting

CS 23.2165 Performance and flight characteristics requirements for flight in icing conditions

ED Decision 2017/013/R

- (a) An applicant who requests certification for flight in icing conditions must show the following in the icing conditions for which certification is requested under normal operation of the ice protection system(s):
- (1) comply with each requirement of this Subpart, except those applicable to spins and any that must be demonstrated at speeds in excess of:
 - (i) 250 knots calibrated airspeed (KCAS);
 - (ii) V_{MO} or M_{MO} or V_{NE} ; or
 - (iii) a speed at which the applicant demonstrates the airframe will be free of ice accretion;

- (2) the means by which stall warning is provided to the pilot for flight in icing conditions and non-icing conditions is the same.
- (b) If an applicant requests certification for flight in icing conditions, the applicant must provide a means to detect any icing conditions for which certification is not requested and demonstrate the aeroplane's ability to avoid or exit those conditions.
- (c) The applicant must develop an operating limitation to prohibit intentional flight, including take-off and landing, into icing conditions for which the aeroplane is not certified to operate.

AMC1 23.2165 Performance and flight characteristics requirements for flight in icing conditions

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.14 Performance and Flight Characteristics Requirements for Flight in Icing Conditions

[F3120/F3120M-20](#) Standard Specification for Ice Protection for General Aviation Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2165 Performance and flight characteristics requirements for flight in icing conditions

ED Decision 2023/002/R

CS-23 Amdt 4

23.1419 Ice Protection

Following the cancellation of Federal Aviation Administration (FAA) Advisory Circular (AC)-1419-2D, applicants should now use [AMC1 23.2165](#).

AMC3 23.2165 Performance and flight characteristics requirements for flight in icing conditions

ED Decision 2017/025/R

None

FLIGHT INFORMATION

CS 23.2170 Operating limitations

ED Decision 2017/013/R

- (a) The following flight information is established:
- (1) operating limitations, procedures and instructions necessary for the safe operation of the aeroplane; and
 - (2) essential speed and performance information.

AMC1 23.2170 Operating limitations

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

5.15 Operating Limitations

[F3174/F3174M-21](#) Standard Specification for Establishing Operating Limitations and Information for Aeroplanes

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2170 Operating limitations

ED Decision 2017/025/R

CS-23 Amdt 4

23.1501 General

23.1505 Airspeed limitations

23.1507 Manoeuvring speed

23.1511 Flap extended speed

23.1513 Minimum control speed

23.1519 Weight and centre of gravity

23.1527 Maximum operating altitude

AMC3 23.2170 Operating limitations

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.1501 General

VLA.1505 Airspeed limitations

VLA.1507 Manoeuvring speed

VLA.1511 Flap extended speed

VLA.1519 Weight and centre of gravity

SUBPART C — STRUCTURES

CS 23.2200 Structural design envelope

ED Decision 2017/013/R

The applicant must determine the structural design envelope, which describes the range and limits of aeroplane design and operational parameters for which the applicant will show compliance with the requirements of this Subpart. The applicant must account for all aeroplane design and operational parameters that affect structural loads, strength, durability, and aeroelasticity, including:

- (a) structural design airspeeds to be considered when determining the corresponding manoeuvring and gust loads must:
 - (1) be sufficiently greater than the stalling speed of the aeroplane to safeguard against loss of control in turbulent air; and
 - (2) provide sufficient margin for the establishment of practical operational limiting airspeeds.
- (b) flight load conditions to be expected in service;
- (c) mass variations and distributions over the applicable mass and centre of gravity envelope, within the operating limitations;
- (d) loads in response to all designed control inputs; and
- (e) redistribution of loads if deflections under load would significantly change the distribution of external or internal loads.

AMC1 23.2200 Structural design envelope

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.1 Structural Design Envelope

[F3116/F3116M-24](#) Standard Specification for Design Loads and Conditions

[F3396/F3396M-20](#) Standard Practice for Aircraft Simplified Loads Criteria

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2200 Structural design envelope

ED Decision 2017/025/R

CS-23 Amdt 4

23.321(b), (c) Flight Loads - General

23.333(a), (b), (d) Flight envelope

23.335 Design airspeeds

23.337 Limit manoeuvring load factors

23.341 Gust load factors

AMC3 23.2200 Structural design envelope

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.321 Flight Loads - General

VLA.333 Flight envelope

VLA.335 Design airspeeds

VLA.337 Limit manoeuvring load factors

VLA.341 Gust load factors

CS 23.2205 Interaction of systems and structures

ED Decision 2017/013/R

For aeroplanes equipped with systems that affect structural performance, either directly or as a result of failure or malfunction, the applicant must account for the influence and failure conditions of these systems when showing compliance with the requirements of this Subpart.

AMC1 23.2205 Interaction of systems and structures

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.2 Interaction of Systems and Structure

Remarks

[F3254-22](#) Standard Specification for Aircraft Interaction of Systems and Structures

To demonstrate compliance with 23.2205, the following of F3254-22 should be adjusted.

Chapter 4 - Interaction of System and Structure:

Modifications are required in Figures 2, 3 and 4:

- Replace the probability label 'remote' with ' 10^{-5} '
- Replace the label 'Extremely Improbable' as follows:
 - for Level 1, 2 and 3 aeroplanes, use ' 10^{-8} '
 - for Level 4 aeroplanes, use ' 10^{-9} '

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2205 Interaction of systems and structures

ED Decision 2017/025/R

None

Remarks

Provision not included in CS 23 Amdt 4

AMC3 23.2205 Interaction of systems and structures

ED Decision 2017/025/R

None

Remarks

Provision not included in CS VLA Amdt 1

STRUCTURAL LOADS

CS 23.2210 Structural design loads

ED Decision 2017/013/R

- (a) The applicant must:
- (1) determine structural design loads resulting from likely externally or internally applied pressure, force or moment which may occur in flight, ground and water operations, ground- and water- handling, and while the aeroplane is parked or moored;
 - (2) determine the loads required by CS 23.2210(a)(1) at all critical combinations of parameters, on and within the boundaries of the structural design envelope; and
 - (3) the magnitude and distribution of these loads must be based on established physical principles within the structural design envelope.

AMC1 23.2210 Structural-design loads

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.3 Structural Design Loads

[F3116/F3116M-24](#) Standard Specification for Design Loads and Conditions

[F3396/F3396M-20](#) Standard Practice for Aircraft Simplified Loads Criteria

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2210 Structural-design loads

ED Decision 2017/025/R

CS-23 Amdt 4

23.301(b), (c), (d) Loads (With Appendix A)

23.321(a) Flight Loads - General

23.343 Design fuel loads

23.345 High lift devices

23.471 Ground Loads - General

23.473 Ground load conditions and assumptions

23.507 Jacking loads

23.509 Towing loads

23.511 Ground load: unsymmetrical loads on multiple-wheel units

23.521 Water load conditions

23.523 Design weights and center of gravity positions

23.525 Application of loads

23.527 Hull and main float load factors (With Appendix I)

23.537 Seawing loads

23.753 Main float Design

AMC3 23.2210 Structural-design loads

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.301 Loads (With Appendix A)

VLA.321 Flight Loads - General

VLA.345 High lift devices

VLA.471 Ground Loads - General

VLA.473 Ground load conditions and assumptions

VLA.521 Water load conditions

CS 23.2215 Flight load conditions

ED Decision 2017/013/R

- (a) Critical flight loads are established for symmetrical and asymmetrical loading from all combinations of airspeeds and load factors at and within the boundaries of the manoeuvre and gust envelope:
 - (1) at each altitude within the operating limitations, where the effects of compressibility are taken into account when significant;
 - (2) at each mass from the design minimum mass to the design maximum mass; and
 - (3) at any practical but conservative distribution of disposable load within the operating limitations for each altitude and weight.
- (b) Vibration and buffeting does not result in structural damage up to dive speed.
- (c) Flight loads resulting from a likely failure of an aeroplane system, component, or engine are determined.

AMC1 23.2215 Flight load conditions

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.4 Flight Load Conditions

[F3116/F3116M-24](#) Standard Specification for Design Loads and Conditions

[F3396/F3396M-20](#) Standard Practice for Aircraft Simplified Loads Criteria

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2215 Flight load conditions

ED Decision 2026/003/R

CS-23 Amdt 4

- 23.331 Symmetrical flight conditions
- 23.333(c) Flight envelope
- 23.347 Unsymmetrical flight loads
- 23.349 Rolling conditions
- 23.351 Yawing conditions
- 23.367 Unsymmetrical loads due to engine failure

[AMC & GM to CS-23: Issue 5]

AMC3 23.2215 Flight load conditions

ED Decision 2026/003/R

CS VLA Amdt 1

- VLA.331 Symmetrical flight conditions
- VLA.333 Flight envelope
- VLA.347 Unsymmetrical flight loads
- VLA.349 Rolling conditions
- VLA.351 Yawing conditions

[AMC & GM to CS-23: Issue 5]

CS 23.2220 Ground and water load conditions

ED Decision 2017/013/R

The applicant must determine the structural design loads resulting from taxi, take-off, landing, and handling conditions on the applicable surface in normal and adverse attitudes and configurations.

AMC1 23.2220 Ground and water load conditions

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.5 Ground and Water Load Conditions

[F3116/F3116M-24](#) Standard Specification for Design Loads and Conditions

[F3331-18](#) Standard Practice for Aircraft Water Loads

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2220 Ground and water load conditions

ED Decision 2017/025/R

CS-23 Amdt 4

- 23.477 Landing gear arrangement (With Appendix C)
- 23.479 level landing conditions (With Appendix C, D)
- 23.481 Tail down landing conditions
- 23.483 One-wheel landing conditions
- 23.485 Side load conditions
- 23.493 Braked roll conditions
- 23.505 Supplementary conditions for skiplanes
- 23.529 Hull and main float landing conditions
- 23.531 Hull and main float takeoff conditions
- 23.731 Wheels

AMC3 23.2220 Ground and water load conditions

ED Decision 2017/025/R

CS VLA Amdt 1

- VLA.477 Landing gear arrangement (With Appendix C)
- VLA.479 level landing conditions
- VLA.481 Tail down landing conditions
- VLA.483 One-wheel landing conditions
- VLA.485 Side load conditions
- VLA.493 Braked roll conditions
- VLA.505 Supplementary conditions for skiplanes
- VLA.731 Wheels

CS 23.2225 Component loading conditions

ED Decision 2017/013/R

- (a) The applicant must determine the loads acting upon all relevant structural components, in response to:
 - (1) interaction of systems and structures;
 - (2) structural design loads;
 - (3) flight load conditions; and
 - (4) ground and water load conditions.
- (b) The complete pressurised cabin, including doors, windows, canopy and valves, is exposed as a pressure vessel for the maximum relief valve setting multiplied by a factor of 1.33, without considering other loads.

AMC1 23.2225 Component loading conditions

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.6 Component Loading Conditions

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3232/F3232M-25](#) Standard Specification for Flight Controls in Small Aircraft

[F3116/F3116M-24](#) Standard Specification for Design Loads and Conditions

[F3396/F3396M-20](#) Standard Practice for Aircraft Simplified Loads Criteria

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2225 Component loading conditions

ED Decision 2017/025/R

CS-23 Amdt 4

23.302 Canard or tandem wing configurations

23.361 Engine torque

23.363 Side load on engine mount

23.365 Pressurized cabin loads

23.369 Rear lift truss

23.371 Gyroscopic and aerodynamic loads

23.373 Speed control devices

23.391 Control surface loads

23.393 Loads parallel to hinge line

23.395 Control system loads

23.397 Limit control forces and torques

23.399 Dual control system

23.405 Secondary control system

23.407 Trim tab effects

23.409 Tabs

23.415 Ground gust conditions

23.421 Balancing loads

23.423 Manoeuvring loads

23.425 Gust loads

23.427 Unsymmetrical loads

23.441 Manoeuvring loads

23.443 Gust loads

23.445 Outboard fins or winglets
23.455 Ailerons
23.459 Special devices
23.497 Supplementary conditions for tail wheels
23.499 Supplementary conditions for nose wheels
23.533 Hull and main float bottom pressures (With Appendix I)
23.535 Auxiliary float loads
23.659 Mass Balance

AMC3 23.2225 Component loading conditions

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.361 Engine torque
VLA.363 Side load on engine mount
VLA.369 Rear lift truss
VLA.373 Speed control devices
VLA.391 Control surface loads (*With Appendix B*)
VLA.395 Control system loads
VLA.397 Limit control forces and torques
VLA.399 Dual control system
VLA.405 Secondary control system
VLA.407 Trim tab effects
VLA.409 Tabs
VLA.415 Ground gust conditions
VLA.421 Balancing loads (*With Appendix B*)
VLA.423 Manoeuvring loads (*With Appendix B*)
VLA.425 Gust loads
VLA.427 Unsymmetrical loads
VLA.441 Manoeuvring loads (*With Appendix B*)
VLA.443 Gust loads (*With Appendix B*)
VLA.445 Outboard fins or winglets
VLA.447 Combined loads on tail surfaces
VLA.449 Additional loads applicable to V-tails
VLA.455 Ailerons (*With Appendix B*)
VLA.457 Wing flaps

VLA.459 Special devices

VLA.497 Supplementary conditions for tail wheels

VLA.499 Supplementary conditions for nose wheels

VLA.659 Mass Balance

CS 23.2230 Limit and ultimate loads

ED Decision 2017/013/R

- (a) Unless special or other factors of safety are necessary to meet the requirements of this Subpart, the applicant must determine:
 - (1) the limit loads, which are equal to the structural design loads; and
 - (2) the ultimate loads, which are equal to the limit loads multiplied by a 1.5 factor of safety, unless otherwise provided.
- (b) Some strength specifications are specified in terms of ultimate loads only, when permanent detrimental deformation is acceptable.

AMC1 23.2230 Limit and ultimate loads

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.7 *Limit and Ultimate Loads*

[F3114-21](#) Standard Specification for Structures

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2230 Limit and ultimate loads

ED Decision 2017/025/R

CS-23 Amdt 4

23.301(a) Loads

23.303 Factors of safety

AMC3 23.2230 Limit and ultimate loads

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.301 Loads

VLA.303 Factors of safety

STRUCTURAL PERFORMANCE

CS 23.2235 Structural strength

ED Decision 2017/013/R

The structure must support:

- (a) limit loads without:
 - (1) interference with the safe operation of the aeroplane; and
 - (2) detrimental permanent deformation.
- (b) ultimate loads.

AMC1 23.2235 Structural strength

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.8 *Structural Strength*

[F3114-21](#) Standard Specification for Structures

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2235 Structural strength

ED Decision 2017/025/R

CS-23 Amdt 4

23.305 Strength and deformation

23.307 Proof of structure

23.641 Proof of strength - Wings

23.651 Proof of strength - Control surfaces

23.659 Mass Balance

23.681 (a) Limit load static tests - Control System

23.723 Shock absorption tests

23.725 Limit drop tests

23.726 Ground load dynamic tests

23.727 Reserve energy absorption drop tests

23.729(a) Landing gear extension and retraction system

23.737 Skis

23.843(a) Pressurization tests

23.1435(a)(1) Hydraulic Systems

AMC3 23.2235 Structural strength

ED Decision 2017/025/R

CS VLA Amdt 1

- VLA.305 Strength and deformation
- VLA.307 Proof of structure
- VLA.641 Proof of strength - Wings
- VLA.651 Proof of strength - Control surfaces
- VLA.659 Mass Balance
- VLA.681 Limit load static tests - Control System
- VLA.723 Shock absorption tests
- VLA.725 Limit drop tests
- VLA.726 Ground load dynamic tests
- VLA.727 Reserve energy absorption drop tests
- VLA.729 Landing gear extension and retraction system
- VLA.737 Skis
- VLA.1436 Hydraulic manually-powered brake systems

CS 23.2240 Structural durability

ED Decision 2017/013/R

- (a) The applicant must develop and implement inspections or other procedures to prevent structural failures due to foreseeable causes of strength degradation, which could result in serious or fatal injuries, or extended periods of operation with reduced safety margins. Each of the inspections or other procedures developed under CS 23.2240 must be included in the Airworthiness Limitations Section of the Instructions for Continued Airworthiness required by [CS 23.2625](#).
- (b) For Level-4 aeroplanes, the procedures developed for compliance with CS 23.2240(a) must be capable of detecting structural damage before the damage could result in structural failure.
- (c) For pressurised aeroplanes:
 - (1) the aeroplane must be capable of continued safe flight and landing following a sudden release of cabin pressure, including sudden releases caused by door and window failures;
 - (2) for aeroplanes with maximum operating altitude greater than 12 497 m (41 000 ft), the procedures developed for compliance with CS 23.2240(a) must be capable of detecting damage to the pressurised cabin structure before the damage could result in rapid decompression that would result in serious or fatal injuries.
- (d) The aeroplane must be designed to minimise hazards to the aeroplane due to structural damage caused by high-energy fragments from an uncontained engine or rotating-machinery failure.

AMC1 23.2240 Structural durability

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.9 Structural Durability & 9.11 Equipment Containing High-Energy Rotors

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation

[F3115/F3115M-15](#) Standard Specification for Structural Durability for Small Aeroplanes

[F3380-19](#) Standard Practice for Structural Compliance of Very Light Aeroplanes

[F3116/F3116M-24](#) Standard Specification for Design Loads and Conditions

[F3498-21](#) Standard Practice for Developing Simplified Fatigue Load Spectra

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2240 Structural durability

ED Decision 2017/025/R

CS-23 Amdt 4

23.571 Metallic pressurized cabin structures

23.572 Metallic wing, empennage, and associated structures

23.573 Damage tolerance and fatigue evaluation of structure

23.574 Metallic damage tolerance and fatigue evaluation of commuter category airplanes

23.575 Inspections and other procedures

23.627 Fatigue strength

23.1461 Equipment containing high-energy rotors

AMC3 23.2240 Structural durability

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.572 Metallic wing, empennage, and associated structures

VLA.627 Fatigue strength

CS 23.2245 Aeroelasticity

ED Decision 2017/013/R

(a) The aeroplane must be free from flutter, control reversal, and divergence:

- (1) at all speeds within and sufficiently beyond the structural design envelope;
- (2) for any configuration and condition of operation;
- (3) accounting for critical degrees of freedom; and
- (4) accounting for any critical failures or malfunctions.

- (b) The applicants' design must account for tolerances for all quantities that affect flutter.

AMC1 23.2245 Aeroelasticity

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.10 Aeroelasticity

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3093/F3093M-21](#) Standard Specification for Aeroelasticity Requirements

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2245 Aeroelasticity

ED Decision 2017/025/R

CS-23 Amdt 4

23.629 Flutter

23.687 Spring devices

23.677(c) Trim systems

AMC3 23.2245 Aeroelasticity

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.629 Flutter

VLA.687 Spring devices

VLA.677 Trim systems

CS 23.2250 Design and construction principles

ED Decision 2017/013/R

- (a) Each part, article, and assembly must be designed for the expected operating conditions of the aeroplane.
- (b) Design data must adequately define the part, article, or assembly configuration, its design features, and any materials and processes used.
- (c) The suitability of each design detail and part having an important bearing on safety in operations must be determined.
- (d) The control system must be free from jamming, excessive friction, and excessive deflection when the aeroplane is subjected to expected limit air loads.
- (e) Doors, canopies, and exits must be protected against inadvertent opening in flight, unless shown to create no hazard, when opened in flight.

AMC1 23.2250 Design and construction principles

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.11 Design and Construction Principles

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3232/F3232M-25](#) Standard Specification for Flight Controls in Small Aircraft

[F3114-21](#) Standard Specification for Structures

[F3380-19](#) Standard Practice for Structural Compliance of Very Light Aeroplanes

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2250 Design and construction principles

ED Decision 2017/025/R

CS-23 Amdt 4

23.601 General

23.603 Materials and workmanship

23.683 Operation tests

23.687 Spring devices

23.689 Cable systems

23.731 Wheels

23.733(a), (c) Tires

23.735(b) Brakes

23.775(b), (c), (d) Windshields and windows

23.783(b), (c)(1), (e) Doors

23.807(d)(2) Emergency Exits

23.859(b) through (i) Combustion heater fire protection

23.1323 Airspeed indicating system

23.1325(a) through (e) Static Pressure System

23.1435(a)(3), (c) Hydraulic Systems

23.1445(a), (b) Oxygen distribution system

AMC3 23.2250 Design and construction principles

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.601 General

VLA.603 Materials and workmanship
VLA.683 Operation tests
VLA.687 Spring devices
VLA.689 Cable systems
VLA.731 Wheels
VLA.733 Tires
VLA.735 Brakes
VLA.775 Windshields and windows
VLA.783 Exits
VLA.807 Emergency Exits
VLA.1323 Airspeed indicating system
VLA.1325 Static Pressure System
VLA.1436 Hydraulic manually-powered brake systems

CS 23.2255 Protection of structure

ED Decision 2017/013/R

- (a) Each part of the aeroplane, including small parts such as fasteners, must be protected against deterioration or loss of strength due to any cause likely to occur in the expected operational environment.
- (b) Each part of the aeroplane must have adequate provisions for ventilation and drainage.
- (c) For each part that requires maintenance, preventive maintenance, or servicing, the applicant must incorporate a means into the aeroplane design to allow such actions to be accomplished.

AMC1 23.2255 Protection of structure

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.12 Protection of Structure

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3232/F3232M-25](#) Standard Specification for Flight Controls in Small Aircraft

[F3114-21](#) Standard Specification for Structures

[F3380-19](#) Standard Practice for Structural Compliance of Very Light Aeroplanes

[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2255 Protection of structure

ED Decision 2017/025/R

CS-23 Amdt 4

23.607 Fasteners

23.609 Protection of Structure

23.611 Accessibility

23.689(a)(3) Cable systems

AMC3 23.2255 Protection of structure

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.607 Self-locking nuts

VLA.609 Protection of Structure

VLA.611 Accessibility

VLA.689 Cable systems

CS 23.2260 Materials and processes

ED Decision 2017/013/R

- (a) The applicant must determine the suitability and durability of materials used for parts, articles, and assemblies, the failure of which could prevent continued safe flight and landing, accounting for the effects of likely environmental conditions expected in service.
- (b) The methods and processes of fabrication and assembly used must produce consistently sound structures. If a fabrication process requires close control to reach this objective, the applicant must define the process with an approved process specification as part of the design data.
- (c) Except as provided for in CS 23.2260(f) and (g), the applicant must select design values that ensure material strength with probabilities that account for the criticality of the structural element. Design values must account for the probability of structural failure due to material variability.
- (d) If material strength properties are required, a determination of those properties must be based on sufficient tests of material meeting specifications to establish design values on a statistical basis.
- (e) If thermal effects are significant on a critical component or structure under normal operating conditions, the applicant must determine those effects.
- (f) Design values, greater than the minimums specified by CS 23.2260, may be used, where only guaranteed minimum values are normally allowed, if a specimen of each individual item is tested before use to determine that the actual strength properties of that particular item will equal or exceed those used in the design.
- (g) An applicant may use other material design values if specifically approved by EASA.

AMC1 23.2260 Materials and processes

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.13 Materials and Processes

[F3114-21](#) Standard Specification for Structures

[F3380-19](#) Standard Practice for Structural Compliance of Very Light Aeroplanes

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2260 Materials and processes

ED Decision 2017/025/R

CS-23 Amdt 4

23.603 Materials and workmanship

23.605 Fabrication methods

23.613 Material strength properties and design values

AMC3 23.2260 Materials and processes

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.603 Materials and workmanship

VLA.605 Fabrication methods

VLA.613 Material strength properties and design values

CS 23.2265 Special factors of safety

ED Decision 2017/013/R

- (a) The applicant must determine a special factor of safety for each critical design value for each part, article, or assembly for which that critical design value is uncertain, and for each part, article, or assembly that is:
 - (1) likely to deteriorate in service before normal replacement; or
 - (2) subject to appreciable variability because of uncertainties in manufacturing processes or inspection methods.
- (b) The applicant must determine a special factor of safety using quality controls and specifications that account for each:
 - (1) type of application;
 - (2) inspection method;

- (3) structural test requirement;
 - (4) sampling percentage; and
 - (5) process and material control.
- (c) The applicant must multiply the highest pertinent special factor of safety in the design for each part of the structure by each limit load and ultimate load, or ultimate load only, if there is no corresponding limit load, such as occurs with emergency condition loading.

AMC1 23.2265 Special factors of safety

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.14 Special Factors of Safety

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3114-21](#) Standard Specification for Structures

[F3380-19](#) Standard Practice for Structural Compliance of Very Light Aeroplanes

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2265 Special factors of safety

ED Decision 2017/025/R

CS-23 Amdt 4

23.619 Special factors

23.621 Casting factors

23.623 Bearing factors

23.625 Fitting factors

23.657 Hinges

23.681(b) Limit load static tests - Control System

23.693 Joints

23.785 Seats, berths, litters, safety belts, and shoulder harnesses

AMC3 23.2265 Special factors of safety

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.619 Special factors

VLA.621 Casting factors

VLA.623 Bearing factors

VLA.625 Fitting factors

VLA.657 Hinges

VLA.681 Limit load static tests - Control System

VLA.693 Joints

VLA.785 Seats, safety belts, and harnesses

STRUCTURAL OCCUPANT PROTECTION

CS 23.2270 Emergency conditions

ED Decision 2017/013/R

- (a) The aeroplane, even when damaged in an emergency landing, must protect each occupant against injury that would preclude egress when:
 - (1) properly using safety equipment and features provided for in the design;
 - (2) the occupant experiences ultimate static inertia loads likely to occur in an emergency landing; and
 - (3) items of mass, including engines or auxiliary power units (APUs), within or aft of the cabin, that could injure an occupant, experience ultimate static inertia loads likely to occur in an emergency landing.
- (b) The emergency landing conditions specified in CS 23.2270(a) must:
 - (1) include dynamic conditions that are likely to occur in an emergency landing; and
 - (2) not generate loads experienced by the occupants, which exceed established human-injury criteria for human tolerance due to restraint or contact with objects in the aeroplane.
- (c) The aeroplane must provide protection for all occupants, accounting for likely flight, ground, and emergency landing conditions.
- (d) Each occupant protection system must perform its intended function and not create a hazard that could cause a secondary injury to an occupant. The occupant protection system must not prevent occupant egress or interfere with the operation of the aeroplane when not in use.
- (e) Each baggage and cargo compartment must:
 - (1) be designed for its maximum loading and for the critical load distributions at the maximum load factors corresponding to the flight and ground load conditions determined under this CS;
 - (2) have a means to prevent the contents of the compartment from becoming a hazard by impacting occupants or shifting; and
 - (3) protect controls, wiring, lines, equipment, or accessories whose damage or failure would prevent continued safe flight and landing.

AMC1 23.2270 Emergency conditions

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

6.15 Emergency Conditions

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3232/F3232M-25](#) Standard Specification for Flight Controls in Small Aircraft

[F3083/F3083M-20a](#) Standard Specification for Emergency Conditions, Occupant Safety and Accommodations

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2270 Emergency Conditions

ED Decision 2017/025/R

CS-23 Amdt 4

23.561 Emergency Landing Conditions - General (With Appendix J)

23.562 Emergency landing dynamic conditions

23.785 Seats, berths, litters, safety belts, and shoulder harnesses

23.787 Baggage and cargo compartments

23.1411(b) Safety equipment - General

AMC3 23.2270 Emergency Conditions

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.561 Emergency Landing Conditions - General

VLA.785 Seats, safety belts, and harnesses

VLA.787 Baggage compartments

VLA.1411 Safety equipment - General

SUBPART D — DESIGN AND CONSTRUCTION

CS 23.2300 Flight control systems

ED Decision 2017/013/R

- (a) The flight control systems are designed to:
 - (1) operate easily, smoothly, and positively enough to allow proper performance of their functions;
 - (2) protect against likely hazards.
- (b) Trim systems, if installed, are designed to:
 - (1) protect against inadvertent, incorrect, or abrupt trim operation;
 - (2) provide information that is required for safe operation.

AMC1 23.2300 Flight control systems

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

7.1 Flight Control Systems

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3232/F3232M-25](#) Standard Specification for Flight Controls in Small Aircraft

[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

Remarks

Except as follows:

For Level 1 single-engine aeroplanes with a stall speed in the landing configuration (V_{S0}) of more than 45 knots, ASTM F3264-24, paragraph 7.1 does not include means for showing that the aeroplane is protected from loss of control when any one connecting or transmitting element in the primary flight control system fails. If applying for certification of a Level 1 single-engine aeroplane with a V_{S0} greater than 45 knots, applicants may use the requirements of CS 23.677(b)(1) at Amendment 4 as a means of complying with this aspect of [CS 23.2300](#), or may propose a different means of compliance in accordance with [CS 23.2010](#).

For powered trim, applicants may use the provisions of CS 23.677(d) at Amendment 4 as a means of complying with [CS 23.2010](#).

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2300 Flight control systems

ED Decision 2017/025/R

CS-23 Amdt 4

23.655 Installation

23.671(a) Control systems - General

23.672(b), (c) Stability augmentation and automatic and power-operated systems

23.673 Primary flight controls

23.675 Stops

23.677(a), (b) Trim systems

23.679(c) Control system locks

23.683 Operation tests

23.685 Control system details

23.687 Spring devices

23.697 Wing flap controls

23.701 Flap interconnection

23.1329(b) Automatic Pilot System

AMC3 23.2300 Flight control systems

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.655 Installation

VLA.671 Control systems - General

VLA.673 Primary flight controls

VLA.675 Stops

VLA.677 Trim systems

VLA.679 Control system locks

VLA.683 Operation tests

VLA.685 Control system details

VLA.687 Spring devices

VLA.697 Wing flap controls

VLA.701 Flap interconnection

CS 23.2305 Landing gear systems

ED Decision 2017/013/R

- (a) The landing gear is designed to:
 - (1) provide stable support and control to the aeroplane during surface operation; and
 - (2) account for likely system failures and likely operation environment (including anticipated limitation exceedances and emergency procedures).
- (b) Aeroplanes must have a reliable means of stopping the aeroplane with sufficient kinetic energy absorption to account for landing. Aeroplanes that are required to demonstrate aborted take-off capability must account for this additional kinetic energy.

- (c) For aeroplanes that have a system that actuates the landing gear, there is:
- (1) a positive means to keep the landing gear in the landing position; and
 - (2) an alternative means available to bring the landing gear in the landing position when a non-deployed system position would be a hazard.

AMC1 23.2305 Landing gear systems

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

7.2 Landing Gear Systems

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2305 Landing gear systems

ED Decision 2017/025/R

CS-23 Amdt 4

23.721 General

23.729(b), (c), (g) Landing gear extension and retraction system

23.735(a), (b), (c), (e) Brakes

23.745 Nose/Tail wheel steering

AMC3 23.2305 Landing gear systems

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.729 Landing gear extension and retraction system

VLA.735 Brakes

CS 23.2310 Buoyancy for seaplanes and amphibians

ED Decision 2017/013/R

Aeroplanes intended for operations on water must:

- (a) provide buoyancy of 80 % in excess of the buoyancy required to support the maximum weight of the aeroplane in fresh water; and
- (b) have sufficient margin so that the aeroplane will stay afloat at rest in calm water without capsizing in case of a likely float or hull flooding.

AMC1 23.2310 Buoyancy for seaplanes and amphibians

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification7.3 *Buoyancy for Seaplanes and Amphibians*[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2310 Buoyancy for seaplanes and amphibians

ED Decision 2017/025/R

CS-23 Amdt 4

23.751 Main float buoyancy

23.755 Hulls

23.757 Auxiliary floats

AMC3 23.2310 Buoyancy for seaplanes and amphibians

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.751 Main float buoyancy

VLA.757 Auxiliary floats

OCCUPANT SYSTEM DESIGN PROTECTION

CS 23.2315 Means of egress and emergency exits

ED Decision 2017/013/R

- (a) With the cabin configured for take-off or landing, the aeroplane is designed to:
 - (1) Facilitate rapid and safe evacuation of the aeroplane in conditions likely to occur following an emergency landing, excluding ditching for Level-1, Level-2 and single-engine Level-3 aeroplanes.
 - (2) Have means of egress (openings, exits or emergency exits) that can be readily located and opened from the inside and outside. The means of opening must be simple and obvious.
 - (3) Have easy access to emergency exits when present.
- (b) Aeroplanes approved for aerobatics must have a means to egress the aeroplane in flight.

AMC1 23.2315 Means of egress and emergency exits

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

7.4 Means of Egress and Emergency Exits

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3083/F3083M-20a](#) Standard Specification for Emergency Conditions, Occupant Safety and Accommodations

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2315 Means of egress and emergency exits

ED Decision 2017/025/R

CS-23 Amdt 4

23.783(a), (b), (c)(2), (c)(3), (c)(4), (c)(5), (c)(6), (d), (f), (g) Doors

23.787 Baggage and cargo compartments

23.803 Emergency evacuation

23.805 Flight crew emergency exits

23.807(a), (b)(1), (b)(2), (b)(3), (b)(4), (b) (5), (b)(6) (d)(1), (d)(3), (d)(4), (c), (e) Emergency exits

23.811 Emergency exit marking

23.812 Emergency lighting

23.813 Emergency exit access

23.815 Width of aisle

AMC3 23.2315 Means of egress and emergency exits

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.783 Exits

VLA.787 Baggage compartments

VLA.807 Emergency exits

CS 23.2320 Occupant physical environment

ED Decision 2017/013/R

- (a) The applicant must design the aeroplane to:
 - (1) allow clear communication between the flight crew and passengers;
 - (2) protect the pilot against serious injury due to hazards originating from high energy, associated with systems and equipment; and
 - (3) protect the occupants from serious injury due to breakage of windshields, windows, and canopies.
- (b) For Level-4 aeroplanes, each windshield and its supporting structure directly in front of the pilot must withstand, without penetration, the impact equivalent to a two-pound bird when the velocity of the aeroplane is equal to the aeroplane's maximum approach flap speed.
- (c) The aeroplane must provide each occupant with air at a breathable pressure, free of hazardous concentrations of gases, vapours and smoke during normal operations and likely failures.
- (d) If a pressurisation system is installed in the aeroplane, it must be designed to protect against:
 - (1) decompression to an unsafe level; and
 - (2) excessive differential pressure.
- (e) If an oxygen system is installed in the aeroplane, it must:
 - (1) effectively provide oxygen to each user to prevent the effects of hypoxia; and
 - (2) be free from hazards in itself, in its method of operation, and its effect upon other components.

AMC1 23.2320 Occupant physical environment

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification**7.5 Occupant Physical Environment**[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft[F3083/F3083M-20a](#) Standard Specification for Emergency Conditions, Occupant Safety and Accommodations[F3114-21](#) Standard Specification for Structures[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft**Remarks**[F3227/F3227M-25](#) Standard Specification for Environmental Systems in Aircraft

At variance with F3227-25, Oxygen Fire Hazards Analysis is not completely covered in the current ASTM standards. At variance, additional means of compliance have been developed by EASA for the specific application.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2320 Occupant physical environment

ED Decision 2017/025/R

CS-23 Amdt 4

23.831(a), (b), (c) Ventilation

23.841(a), (b)(1), (b)(2), (b)(3), (b)(4), (b)(8), (c), (d)(1), (d)(2), (d)(3) Pressurized cabins

23.843 Pressurization tests

23.771(b), (c) Pilot compartment

23.775(a), (h)(1) Windshields and windows

23.791 Passenger information signs

23.1441 Oxygen Equipment and supply

23.1443 Minimum mass flow of supplemental oxygen

23.1445 Oxygen distribution system

23.1447 Equipment standards for oxygen dispensing units

23.1449 Means for determining use of oxygen

23.1450(a), (b) Chemical oxygen generators

23.1451 Fire protection for oxygen equipment

23.1461 Equipment containing high-energy rotors

AMC3 23.2320 Occupant physical environment

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.831 Ventilation

VLA.771 Pilot compartment

VLA.775 Windshields and windows

FIRE AND HIGH ENERGY PROTECTION

CS 23.2325 Fire protection

ED Decision 2017/013/R

- (a) The aeroplane is designed to minimise the risk of fire initiation due to:
- (1) anticipated heat or energy dissipation or system failures or overheating that are expected to generate heat sufficient to ignite a fire;
 - (2) ignition of flammable fluids, gases or vapours; and
 - (3) fire-propagating or -initiating system characteristics (e.g. oxygen systems).
- (b) The aeroplane is designed to minimise the risk of fire propagation by:
- (1) providing adequate fire or smoke awareness and extinguishing means when practical;
 - (2) application of self-extinguishing, flame-resistant, or fireproof materials that are adequate to the application, location and certification level; or
 - (3) specifying and designing designated fire zones that meet the specifications of [CS 23.2330](#).

AMC1 23.2325 Fire protection

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

7.6 Fire Protection

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3231/F3231M-24](#) Standard Specification for Electrical Systems for Aircraft with Combustion Engine Electrical Power Generation

[F3234/F3234M-21](#) Standard Specification for Exterior Lighting in Small Aircraft

[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation

[F3083/F3083M-20a](#) Standard Specification for Emergency Conditions, Occupant Safety and Accommodations

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

Remarks

ASTM F44 published standards for showing compliance for electrical systems that are installed on aeroplanes with electric or hybrid-electric propulsion systems. EASA has not yet accepted [F3316-19](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2325 Fire protection

ED Decision 2017/025/R

CS-23 Amdt 4

- 23.1453 Protection of oxygen equipment from rupture
- 23.851 Fire extinguishers
- 23.853 Passenger and crew compartment interiors (With Appendix F)
- 23.855 Cargo and baggage compartment fire protection (With Appendix F)
- 23.859(a) Combustion heater fire protection
- 23.863 Flammable Fluid Fire Protection
- 23.1337(a) Powerplant instruments installation
- 23.1351 Electrical system: General
- 23.1359(a), (c) Electrical System fire protection
- 23.1383(d) Taxi and landing lights (With Appendix F)
- 23.1385(d) Position light system installation

AMC3 23.2325 Fire protection

ED Decision 2017/025/R

CS VLA Amdt 1

- VLA.853 Passenger and crew compartment interiors (With Appendix F)
- VLA.857 Electrical bonding
- VLA.863 Flammable Fluid Fire Protection
- VLA.1337 Powerplant instruments installation
- VLA.1351 Electrical system: General
- VLA.1384 External lights

CS 23.2330 Fire protection in designated fire zones

ED Decision 2017/013/R

- (a) Flight controls, engine mounts, and other flight structures within or adjacent to designated fire zones must be capable of withstanding the effects of a fire.
- (b) A fire in a designated fire zone must not preclude continued safe flight and landing.
- (c) Terminals, equipment, and electrical cables used during emergency procedures must be fire-resistant.

AMC1 23.2330 Fire protection in designated fire zones

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

7.7 Fire Protection in Designated Fire Zones and Adjacent Areas

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3231/F3231M-24](#) Standard Specification for Electrical Systems for Aircraft with Combustion Engine Electrical Power Generation

[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation

[F3114-21](#) Standard Specification for Structures

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2330 Fire protection in designated fire zones

ED Decision 2017/025/R

CS-23 Amdt 4

23.865 Fire protection of flight controls, engine mounts, and other flight structure

23.1359(a), (b) Electrical System fire protection (With Appendix F)

23.1365(b) Electrical Cables and equipment

AMC3 23.2330 Fire protection in designated fire zones

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.865 Fire protection of flight controls and other flight structure

VLA.1365 Electrical Cables and equipment

CS 23.2335 Lightning protection

ED Decision 2017/013/R

For operations where the exposure to lightning is likely, the aeroplane must be protected against catastrophic effects of lightning.

AMC1 23.2335 Lightning protection

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

7.8 Lightning Protection

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2335 Lightning protection

ED Decision 2017/025/R

CS-23 Amdt 4

23.867 Electrical bonding and protection against lightning and static electricity

23.1365 Electrical Cables and equipment

AMC3 23.2335 Lightning protection

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.857 Electrical bonding

VLA.1365 Electrical Cables and equipment

CS 23.2340 Design and construction information

ED Decision 2017/013/R

The following design and construction information is established:

- (a) operating limitations, procedures and instructions necessary for the safe operation of the aeroplane;
- (b) the need for instrument markings or placards;
- (c) any additional information necessary for the safe operation of the aeroplane; and
- (d) inspections or maintenance to assure continued safe operation.

AMC1 23.2340 Design and construction information

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

7.9 Design and Construction Information

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2340 Design and construction information

ED Decision 2017/025/R

CS-23 Amdt 4

23.1523 Minimum Flight Crew

23.1524 Maximum passenger seating configuration

23.1529 Instructions for continued airworthiness (With Appendix G)

23.1541 Markings and placards: General

AMC3 23.2340 Design and construction information

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.1529 Instructions for continued airworthiness

VLA.1541 Markings and placards: General

SUBPART E — POWERPLANT INSTALLATION

CS 23.2400 Powerplant installation

ED Decision 2017/013/R

- (a) For the purpose of this Subpart, the aeroplane powerplant installation must include each component that is necessary for propulsion, affects propulsion safety, or provides auxiliary power to the aeroplane.
- (b) Each aeroplane engine, propeller and auxiliary power unit (APU) must be type certified, or meet accepted specifications.
- (c) The applicant must construct and arrange each powerplant installation to account for:
 - (1) all likely operating conditions, including foreign object threats;
 - (2) sufficient clearance of moving parts to other aeroplane parts and their surroundings;
 - (3) likely hazards in operation, including hazards to ground personnel; and
 - (4) vibration and fatigue.
- (d) Hazardous accumulations of fluids, vapours or gases are isolated from the aeroplane and personnel compartments and are safely contained or discharged.
- (e) Installations of powerplant components that deviate from the component limitations or installation instructions must be shown to be safe.
- (f) For the purposes of this Subpart, 'energy' means any type of energy for the powerplant, including, for example, fuels of any kind or electric current.

AMC1 23.2400 Powerplant installation

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

8.1 Powerplant Installation

[F3062/F3062M-20](#) Standard Specification for Aircraft Powerplant Installation

[F3063/F3063M-21](#) Standard Specification for Aircraft Fuel Storage and Delivery

[F3064/F3064M-21](#) Standard Specification for Aircraft Powerplant Control, Operation, and Indication

[F3065/F3065M-21a](#) Standard Specification for Aircraft Propeller System Installation

[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation

Remarks

ASTM F44 published standards for showing compliance for electric propulsion systems. EASA has not yet accepted [F3239-22a](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2400 Powerplant installation

ED Decision 2019/020/R

CS-23 Amdt 4

- 23.33 Propeller speed and pitch limits
- 23.901 Installation
- 23.903(a), (b), (d) through (g) Engines and auxiliary power units
- 23.905(a), (b), (d) through (h) Propellers
- 23.907 Propeller vibration
- 23.909(a), (c), (d), (e) Turbocharger systems
- 23.925 Propeller clearance
- 23.934 Turbojet and turbofan engine thrust reverser systems tests
- 23.943 Negative acceleration
- 23.951 Fuel System - General
- 23.955 Fuel Flow
- 23.957(b) Flow between interconnected tanks
- 23.963(b), (c) Fuel tanks: general
- 23.967(a), (b) Fuel tank installation
- 23.975 Fuel tank vents and carburettor vapour vents
- 23.979 Pressure fuelling systems
- 23.997(a), (c), (d) Fuel strainer or filter
- 23.999 Fuel system drains
- 23.1001(a) through (f) Fuel jettisoning system
- 23.1011 Oil system General
- 23.1013 Oil tanks
- 23.1015 Oil tank tests
- 23.1017 Oil lines and fittings
- 23.1019 Oil strainer or filter
- 23.1021 Oil system drains
- 23.1023 Oil radiators
- 23.1027 Propeller feathering system
- 23.1041 Cooling – General
- 23.1043 Cooling tests
- 23.1045 Cooling test procedures for turbine engine powered airplanes
- 23.1047 Cooling test procedures for reciprocating engine powered airplanes
- 23.1061 Installation

- 23.1063 Coolant tank tests
- 23.1097 Carburettor de-icing fluid system capacity
- 23.1099 Carburettor de-icing fluid system detail design
- 23.1101 Induction air preheater design
- 23.1103 Induction system ducts
- 23.1105 Induction system screens
- 23.1107 Induction system filters
- 23.1109 Turbocharger bleed air system
- 23.1111 Turbine engine bleed air system
- 23.1121 Exhaust System - General
- 23.1125 Exhaust heat exchangers
- 23.1141(b), (c), (d) Powerplant controls: general
- 23.1163 Powerplant accessories
- 23.1165 Engine ignition systems
- 23.1193 Cowling and nacelle
- 23.1197 Fire extinguishing agents
- 23.1199 Extinguishing agent containers
- 23.1201 Fire extinguishing system materials
- 23.1203(b), (c) Fire detector system

AMC3 23.2400 Powerplant installation

ED Decision 2017/025/R

CS VLA Amdt 1

- VLA.33 Propeller speed and pitch limits
- VLA.901 Installation
- VLA.903 Engine
- VLA.905 Propeller
- VLA.907 Propeller vibration
- VLA.909 Supercharger
- VLA.925 Propeller clearance
- VLA.943 Negative acceleration
- VLA.951 Fuel System - General
- VLA.955 Fuel Flow
- VLA.957 Flow between interconnected tanks
- VLA.963 Fuel tanks: general

VLA.967 Fuel tank installation

VLA.975 Fuel tank vents and carburettor vapour vents

VLA.999 Fuel system drains

VLA.1011 Oil system General

VLA.1013 Oil tanks

VLA.1015 Oil tank tests

VLA.1017 Oil lines and fittings

VLA.1019 Oil strainer or filter

VLA.1021 Oil system drains

VLA.1023 Oil radiators

VLA.1041 Cooling – General

VLA.1047 Cooling test procedures for reciprocating engine powered airplanes

VLA.1061 Installation

VLA.1063 Coolant tank tests

VLA.1101 Carburettor air preheater design

VLA.1103 Induction system ducts

VLA.1105 Induction system screens

VLA.1121 Exhaust System - General

VLA.1125 Exhaust heat exchangers

VLA.1141 Powerplant controls: general

VLA.1163 Powerplant accessories

VLA.1165 Engine ignition systems

VLA.1193 Cowling and nacelle

CS 23.2405 Power or thrust control systems

ED Decision 2017/013/R

Power or thrust control systems are systems that intervene with the power selection commanded by the direct power settings.

- (a) Power or thrust control systems must be designed so no unsafe condition will result during normal operation of the system.
- (b) Any single failure or likely combination of failures of a power or thrust control system must not prevent continued safe flight and landing of the aeroplane.
- (c) Inadvertent operation of a power or thrust control system by the flight crew must be prevented, or if not prevented, must not result in an unsafe condition.
- (d) Unless the failure of an automatic power or thrust control system is 'extremely remote', the system must:
 - (1) provide a means for the flight crew to verify that the system is in an operating condition;

- (2) provide a means for the flight crew to override the automatic function if the hazard outweighs the safety benefits; and
- (3) prevent inadvertent deactivation of the system.

AMC1 23.2405 Power or thrust control systems

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

8.2 Power or Thrust Control Systems & 8.5 Reversing Systems

[F3062/F3062M-20](#) Standard Specification for Aircraft Powerplant Installation[F3064/F3064M-21](#) Standard Specification for Aircraft Powerplant Control, Operation, and Indication[F3065/F3065M-21a](#) Standard Specification for Aircraft Propeller System Installation[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

Remarks

ASTM F44 published standards for showing compliance for electric propulsion systems. EASA has not yet accepted [F3239-22a](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2405 Power or thrust control systems

ED Decision 2017/025/R

CS-23 Amdt 4

23.904 Automatic power reserve system (With Appendix H)

23.933 Reversing systems

AMC3 23.2405 Power or thrust control systems

ED Decision 2017/025/R

None

CS 23.2410 Powerplant installation hazard assessment

ED Decision 2017/013/R

The applicant must assess each installation separately and in relation to other aeroplane systems and installations to show that any hazard resulting from the likely failure of any system component or accessory will not:

- (a) prevent continued safe flight and landing or, if continued safe flight and landing cannot be ensured, the hazards have been minimised;
- (b) cause serious injury that may be avoided; and

- (c) require immediate action by crew members for continued operation of any remaining powerplant system.

AMC1 23.2410 Powerplant installation hazard assessment

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

8.3 Powerplant Installation Hazard Assessment

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3062/F3062M-20](#) Standard Specification for Aircraft Powerplant Installation

[F3063/F3063M-21](#) Standard Specification for Aircraft Fuel Storage and Delivery

[F3064/F3064M-21](#) Standard Specification for Aircraft Powerplant Control, Operation, and Indication

[F3065/F3065M-21a](#) Standard Specification for Aircraft Propeller System Installation

[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

Remarks

ASTM F44 published standards for showing compliance for electric propulsion systems. EASA has not yet accepted [F3239-22a](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2410 Powerplant installation hazard assessment

ED Decision 2017/025/R

CS-23 Amdt 4

23.903(b) through (g) Engines and auxiliary power units

23.909(b), (c) Turbocharger systems

23.937 Powerplant operating characteristics

23.953 Fuel system independence

23.955 Fuel flow

23.959 Unusable fuel supply

23.991 Fuel pumps

23.1001(h) Fuel jettisoning system

23.1011 General

23.1027 Propeller feathering system

23.1109 Turbocharger bleed air system

- 23.1141(e) Powerplant controls: general
- 23.1143(g) Engine controls
- 23.1147 Mixture controls
- 23.1163 Powerplant accessories
- 23.1437 Accessories for twin-engine aeroplanes

AMC3 23.2410 Powerplant installation hazard assessment

ED Decision 2017/025/R

CS VLA Amdt 1

- VLA.903 Engine
- VLA.909 Supercharger
- VLA.955 Fuel flow
- VLA.959 Unusable fuel supply
- VLA.991 Fuel pumps
- VLA.1011 General
- VLA.1141 Powerplant controls: general
- VLA.1143 Engine controls
- VLA.1147 Mixture controls
- VLA.1163 Powerplant accessories

CS 23.2415 Powerplant installation ice protection

ED Decision 2017/013/R

- (a) The aeroplane design must prevent foreseeable accumulation or shedding of ice or snow that adversely affect powerplant operation.
- (b) The powerplant installation design must prevent any accumulation of ice or snow that adversely affects powerplant operation in those icing conditions for which certification is requested.

AMC1 23.2415 Powerplant installation ice protection

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

8.4 Powerplant Installation Ice Protection

[F3062/F3062M-20](#) Standard Specification for Aircraft Powerplant Installation

[F3063/F3063M-21](#) Standard Specification for Aircraft Fuel Storage and Delivery

[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation

Remarks

ASTM F44 published standards for showing compliance for electric propulsion systems. EASA has not yet accepted [F3239-22a](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2415 Powerplant installation ice protection

ED Decision 2023/002/R

CS-23 Amdt 4

- 23.929 Engine installation ice protection
- 23.1093 Induction system icing protection
- 23.975 Fuel tank vents and carburettor vapour vents
- 23.997 Fuel strainer or filter
- 23.1105 Induction system screens

Remarks

Following the cancellation of FAA AC-1419-2D, applicants should now use the icing conditions that are outlined in [AMC1 23.2165](#).

AMC3 23.2415 Powerplant installation ice protection

ED Decision 2017/025/R

CS VLA Amdt 1

- VLA.1093 Induction system icing protection
- VLA.975 Fuel tank vents and carburettor vapour vents
- VLA.1105 Induction system screens

CS 23.2420

ED Decision 2017/013/R

(reserved)

CS 23.2425 Powerplant operational characteristics

ED Decision 2017/013/R

- (a) The installed powerplant must operate without any hazardous characteristics during normal and emergency operation within the range of operation limitations for the aeroplane and powerplant installation.
- (b) The design must allow the shutdown and restart of the powerplant in flight within an established operating envelope.

AMC1 23.2425 Powerplant operational characteristics

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

8.6 Powerplant Operational Characteristics

[F3062/F3062M-20](#) Standard Specification for Aircraft Powerplant Installation

[F3064/F3064M-21](#) Standard Specification for Aircraft Powerplant Control, Operation, and Indication

[F3065/F3065M-21a](#) Standard Specification for Aircraft Propeller System Installation

[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

Remarks

ASTM F44 published standards for showing compliance for electric propulsion systems. EASA has not yet accepted [F3239-22a](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2425 Powerplant operational characteristics

ED Decision 2017/025/R

CS-23 Amdt 4

23.903(b), (d) through (g) Engines

23.905(c) Propellers

23.909(a) Turbocharger systems

23.934 Turbojet and turbofan engine thrust reverser systems tests

23.939 Turbopropeller-drag limiting systems

23.943 Negative acceleration

23.1142 Auxiliary power unit controls

23.1145 Ignition switches

23.1165 Engine ignition systems

AMC3 23.2425 Powerplant operational characteristics

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.903 Engine

VLA.905 Propeller

VLA.909 Supercharger

VLA.943 Negative acceleration

VLA.1145 Ignition switches

VLA.1165 Engine ignition systems

CS 23.2430 Powerplant installation, energy storage and distribution systems

ED Decision 2023/002/R

- (a) Each system must:
- (1) Be designed to provide independence between multiple energy storage and supply systems so that a failure of any one component in one system will not result in the loss of energy storage or supply of another system.
 - (2) Be designed to prevent catastrophic events due to lightning strikes taking into account direct and indirect effects for aeroplanes where the exposure to lightning is likely.
 - (3) Provide energy to the powerplant installation with adequate margins to ensure safe functioning under all permitted and likely operating conditions, and accounting for likely component failures.
 - (4) Provide the information established in [CS 23.2445\(g\)](#) to the flight crew and provide uninterrupted supply of that energy when the system is correctly operated, accounting for likely energy fluctuations.
 - (5) Provide a means to safely remove or isolate the energy stored within the system.
 - (6) Be designed to retain the energy under all likely operating conditions and minimise hazards to the occupants during any survivable emergency landing. For Level-4 aeroplanes, failure due to overload of the landing system must be taken into account.
 - (7) Prevent hazardous contamination of the energy supplied to each powerplant installation.
- (b) Each storage system must:
- (1) withstand the loads under likely operating conditions without failure, accounting for installation;
 - (2) be isolated from personnel compartments and protected from likely hazards;
 - (3) be designed to prevent significant loss of stored energy due to energy transfer or venting under likely operating conditions;
 - (4) provide energy for at least one-half hour of operation at maximum continuous power or thrust; and
 - (5) be capable of jettisoning energy safely if this functionality is provided.
- (c) Each energy-storage-refilling or -recharging system must be designed to:
- (1) prevent improper refilling or recharging;
 - (2) prevent contamination of the stored energy during likely operating conditions; and
 - (3) prevent the occurrence of any hazard to the aeroplane or to persons during refilling or recharging.
- (d) Likely errors during ground handling of the aeroplane must not lead to a hazardous loss of stored energy.

AMC1 23.2430 Powerplant installation, energy storage and distribution systems

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

8.7 Fuel and Energy Storage and Distribution Systems

[F3062/F3062M-20](#) Standard Specification for Aircraft Powerplant Installation[F3063/F3063M-21](#) Standard Specification for Aircraft Fuel Storage and Delivery[F3064/F3064M-21](#) Standard Specification for Aircraft Powerplant Control, Operation, and Indication[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation[F3114-21](#) Standard Specification for Structures[F3397/F3397M](#) Standard Practice for Aeroplane Turbine Fuel System Hot Weather Operations

Remarks

ASTM F44 published standards for showing compliance for electric propulsion systems. EASA has not yet accepted [F3239-22a](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2430 Powerplant installation, energy storage and distribution systems

ED Decision 2017/025/R

CS-23 Amdt 4

23.951 Fuel System - General

23.953 Fuel system independence

23.954 Fuel system lightning protection

23.955 Fuel flow

23.957 Flow between interconnected tanks

23.959 Unusable fuel supply

23.961 Fuel system hot weather operation

23.963(a), (d), (e) Fuel tank: general

23.965 Fuel tank tests

23.967(a), (c), (d), (e) Fuel tank installation

23.969 Fuel tank expansion space

23.971 Fuel tank sump

23.973 Fuel tank filler connection

23.975 Fuel tank vents and carburettor vapour vents

23.977 Fuel tank outlet

23.979 Pressure fuelling systems

23.991 Fuel pumps

23.993 Fuel system lines and fittings

23.994 Fuel system components

23.997(b), (d), (e) Fuel strainer or filter

23.999 Fuel system drains

23.1001(a) through (f) Fuel jettisoning system

23.1337(a) Powerplant instruments installation

23.721 Landing gear systems - General

Remarks

Provisions of AMC2 cover only fuel systems

AMC3 23.2430 Powerplant installation, energy storage and distribution systems

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.951 Fuel System - General

VLA.955 Fuel flow

VLA.957 Flow between interconnected tanks

VLA.959 Unusable fuel supply

VLA.961 Fuel system hot weather operation

VLA.963 Fuel tank: general

VLA.965 Fuel tank tests

VLA.967 Fuel tank installation

VLA.969 Fuel tank expansion space

VLA.971 Fuel tank sump

VLA.973 Fuel tank filler connection

VLA.975 Fuel tank vents and carburettor vapour vents

VLA.977 Fuel strainer or filter

VLA.991 Fuel pumps

VLA.993 Fuel system lines and fittings

VLA.999 Fuel system drains

VLA.1337 Powerplant instruments

Remarks

Provisions of AMC3 cover only fuel systems

CS 23.2435 Powerplant installation support systems

ED Decision 2017/013/R

- (a) Powerplant installation support systems are all systems whose direct purpose is to support the powerplant or the energy storage device in its intended function as part of the powerplant installation.
- (b) Powerplant installation support systems that have a direct effect on the engine availability are considered in the engine reliability.
- (c) Powerplant installation support systems are designed for the operating conditions applicable to the location of installation.
- (d) Systems must be capable of operating under the conditions likely to occur.
- (e) System function and characteristics that have an effect on the powerplant installation system performance are established.
- (f) Ingestion of likely foreign objects that would be hazardous to the engine is prevented.
- (g) The pilot must be aware of the air intake configuration and able to influence it.
- (h) Any likely single failures of powerplant installation support systems that result in a critical loss of thrust are mitigated.

AMC1 23.2435 Powerplant installation support systems

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification**8.8 Powerplant Induction, Exhaust, and Support Systems**

[F3062/F3062M-20](#) Standard Specification for Aircraft Powerplant Installation

Remarks

ASTM F44 published standards for showing compliance for electric propulsion systems. EASA has not yet accepted [F3239-22a](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2435 Powerplant installation support systems

ED Decision 2017/025/R

CS-23 Amdt 4

23.1091 Air induction system

23.1101(a) Induction air preheater design

23.1103(a) through (d) Induction system ducts

23.1111(b) Turbine engine bleed air system

23.1121 Exhaust System - General

23.1123 Exhaust system

23.1125 Exhaust heat exchangers

Remarks

Provisions of AMC2 cover only induction and exhaust systems

AMC3 23.2435 Powerplant installation support systems

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.1091 Air induction

VLA.1101 Carburettor air preheater design

VLA.1103 Induction system ducts

VLA.1121 Exhaust System - General

VLA.1123 Exhaust manifold

VLA.1125 Exhaust heat exchangers

Remarks

Provisions of AMC3 cover only induction and exhaust systems

CS 23.2440 Powerplant installation fire protection

ED Decision 2017/013/R

There must be means to isolate and mitigate hazards to the aeroplane in the event of a powerplant system fire or overheat in operation.

AMC1 23.2440 Powerplant installation fire protection

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

8.9 Powerplant Installation Fire Protection

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3062/F3062M-20](#) Standard Specification for Aircraft Powerplant Installation

[F3063/F3063M-21](#) Standard Specification for Aircraft Fuel Storage and Delivery

[F3064/F3064M-21](#) Standard Specification for Aircraft Powerplant Control, Operation, and Indication

[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation

Remarks

ASTM F44 published standards for showing compliance for electric propulsion systems. EASA has not yet accepted [F3239-22a](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2440 Powerplant installation fire protection

ED Decision 2017/025/R

CS-23 Amdt 4

- 23.995 Fuel valves and controls
- 23.1103(e), (f) Induction system ducts
- 23.1141(f) Powerplant controls: general
- 23.1181 Designated fire zones: regions included
- 23.1182 Nacelle areas behind firewalls
- 23.1183 Lines, fittings, and components
- 23.1189 Shutoff means
- 23.1191 Firewalls
- 23.1192 Engine accessory compartment diaphragm
- 23.1193 Cowling and nacelle
- 23.1195 Fire extinguishing systems
- 23.1197 Fire extinguishing agents
- 23.1201 Fire extinguishing system materials
- 23.1203(a), (e) Fire detector system
- 23.1435(c) Hydraulic Systems

AMC3 23.2440 Powerplant installation fire protection

ED Decision 2017/025/R

CS VLA Amdt 1

- VLA.995 Fuel valves and controls
- VLA.1103 Induction system ducts
- VLA.1141 Powerplant controls and accessories: general
- VLA.1182 Nacelle areas behind firewalls
- VLA.1183 Lines, fittings, and components
- VLA.1191 Firewalls
- VLA.1193 Cowling and nacelle

CS 23.2445 Powerplant installation information

ED Decision 2017/013/R

The following powerplant installation information is established:

- (a) operating limitations, procedures and instructions necessary for the safe operation of the aeroplane;
- (b) the need for instrument markings or placards;
- (c) any additional information necessary for the safe operation of the aeroplane;
- (d) inspections or maintenance to assure continued safe operation;
- (e) information related to the air intake configuration;
- (f) techniques and associated limitations for engine starting and stopping; and
- (g) energy level information to support energy management, including consideration of a likely component failure within the system.

AMC1 23.2445 Powerplant installation information

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

8.10 Powerplant Installation Information

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

[F3174/F3174M-21](#) Standard Specification for Establishing Operating Limitations and Information for Aeroplanes

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2445 Powerplant installation information

ED Decision 2017/025/R

CS-23 Amdt 4

23.1521 Powerplant limitations

23.1522 Auxiliary power unit limitations

23.1529 Instructions for continued airworthiness (With Appendix G)

AMC3 23.2445 Powerplant installation information

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.1521 Powerplant limitations

VLA.1529 Instructions for continued airworthiness

SUBPART F — SYSTEMS AND EQUIPMENT

CS 23.2500 General requirements on systems and equipment function

ED Decision 2017/013/R

- (a) Requirements CS 23.2500, [CS 23.2505](#) and [CS 23.2510](#) are general requirements applicable to systems and equipment installed in the aeroplane, and should not be used to supersede any other specific CS-23 requirement.
- (b) Equipment and systems required to comply with type certification requirements, airspace requirements or operating rules, or whose improper functioning would lead to a hazard, must be designed and installed so that they perform their intended function throughout the operating and environmental limits for which the aeroplane is certified.

AMC1 23.2500 General requirements on systems and equipment function

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

9.1 Systems and Equipment Function Requirements

[F3231/F3231M-24](#) Standard Specification for Electrical Systems for Aircraft with Combustion Engine Electrical Power Generation

[F3235-22](#) Standard Specification for Aircraft Storage Batteries

[F3232/F3232M-25](#) Standard Specification for Flight Controls in Small Aircraft

[F3233/F3233M-23b](#) Standard Specification for Flight and Navigation Instrumentation in Aircraft

[F3229/F3229M-23a](#) Standard Practice for Static Pressure System Tests in Small Aircraft

[F3064/F3064M-21](#) Standard Specification for Aircraft Powerplant Control, Operation, and Indication

[F3066/F3066M-18](#) Standard Specification for Aircraft Powerplant Installation Hazard Mitigation

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

[F3120/F3120M-20](#) Standard Specification for Ice Protection for General Aviation Aircraft

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

Remarks

- [F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft
At variance with F3061-24a, paragraph 4.4.2, use of system level verification is usually not acceptable, and it should be discussed with EASA.
- [F3532-25](#) Standard Practice for Protection of Aircraft Systems from Intentional Unauthorized Electronic Interactions
At variance with F3532 and F3061-24a, paragraph 4.3, for showing compliance with [CS 23.2500\(b\)](#) for equipment and systems whose improper functioning could lead to an intentional unauthorised electronic interaction (IUEI)

- For an aeroplane with assessment level IV, the applicant may consider AMC 20-42.
- For an aeroplane with assessment level I, level II or level III, the applicant may consider ASTM F3532-25.

For an aeroplane with certification level 1, operated in visual flight rules (VFR) day or night, considerations of cybersecurity threats as potential sources of improper functioning of the equipment and systems are not required.

ASTM F44 published standards for showing compliance for electrical systems that are installed on aeroplanes with electric or hybrid-electric propulsion systems. EASA has not yet accepted [F3316-19](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2500 General requirements on systems and equipment function

ED Decision 2019/020/R

CS-23 Amdt 4

- 23.1301 Function and installation
- 23.1303 Flight and navigation instruments
- 23.1305 Powerplant instruments
- 23.1309(a) Equipment, systems, and installations
- 23.1311 Electronic display instrument systems
- 23.1321 Arrangement and visibility
- 23.1323 Airspeed indicating system
- 23.1325 Static pressure system
- 23.1327 Magnetic direction indicator
- 23.1329 Automatic pilot system
- 23.1335 Flight director systems
- 23.1351(b), (e), (f), (g) Electrical Systems - General
- 23.1357 Circuit protective devices
- 23.1361 Master switch arrangement
- 23.1367 Switches
- 23.1381(c) Instrument lights
- 23.1416 Pneumatic de-icer boot system
- 23.729(d) Landing gear extension and retraction system
- 23.843(b) Pressurization tests
- 23.1141(b), (c), (d) Powerplant controls: general

23.1201 Fire extinguishing system materials

23.1203(e) Fire detector system

Remarks

23.1305 must be complemented. F3064-18 § 6.2.1.6 provides this AMC.

AMC3 23.2500 General requirements on systems and equipment function

*ED Decision 2019/020/R***CS VLA Amdt 1**

VLA.1301 Function and installation

VLA.1303 Flight and navigation instruments

VLA.1305 Powerplant instruments

VLA.1307 Miscellaneous equipment

VLA.1309 Equipment, systems, and installations

VLA.1321 Arrangement and visibility

VLA.1323 Airspeed indicating system

VLA.1325 Static pressure system

VLA.1327 Magnetic direction indicator

VLA.1351 Electrical Systems - General

VLA.1357 Circuit protective devices

VLA.1361 Master switch arrangement

VLA.1367 Switches

VLA.729 Landing gear extension and retraction system

VLA.1141 Powerplant controls and accessories: general

Remarks

VLA.1305 must be complemented. F3064-18 § 6.2.1.6 provides this AMC.

CS 23.2505 General requirements on equipment installation

ED Decision 2017/013/R

- (a) Each item of installed equipment is installed according to limitations specified for that equipment.
- (b) On multi-engine aeroplanes, engine-driven accessories essential to safe operation must be distributed among multiple engines.

AMC1 23.2505 General requirements on equipment installation

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification**9.2 Equipment Function and Installation Requirements**[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft[F3231/F3231M-24](#) Standard Specification for Electrical Systems for Aircraft with Combustion Engine Electrical Power Generation[F3235-22](#) Standard Specification for Aircraft Storage Batteries[F3232/F3232M-25](#) Standard Specification for Flight Controls in Small Aircraft[F3233/F3233M-23b](#) Standard Specification for Flight and Navigation Instrumentation in Aircraft[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems**Remarks**

ASTM F44 published standards for showing compliance for electrical systems that are installed on aeroplanes with electric or hybrid-electric propulsion systems. EASA has not yet accepted [F3316-19](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC&GM to CS-23: Issue 4]

[AMC&GM to CS-23: Issue 5]

AMC2 23.2505 General requirements on equipment installation

ED Decision 2017/025/R

CS-23 Amdt 4

23.1301 Function and installation

23.1437 Accessories for twin-engine aeroplanes

AMC3 23.2505 General requirements on equipment installation

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.1301 Function and installation

CS 23.2510 Equipment, systems, and installations

ED Decision 2017/013/R

- (a) The equipment and systems identified in [CS 23.2500](#), considered separately and in relation to other systems, must be designed and installed such that:
- (1) each catastrophic failure condition is extremely improbable; and
 - (2) each hazardous failure condition is extremely remote; and
 - (3) each major failure condition is remote.

- (b) The operation of equipment and systems not covered by [CS 23.2500](#) does not cause a hazard to the aeroplane or its occupants throughout the operating and environmental limits for which the aeroplane is certified.

AMC1 23.2510 Equipment, systems, and installations

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

9.3 Equipment, Systems, and Installation

[F3233/F3233M-23b](#) Standard Specification for Flight and Navigation Instrumentation in Aircraft

[F3309/F3309M-24a](#) Standard Practice for Simplified Safety Assessment of Systems and Equipment in Small Aircraft

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

Remarks

- [F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft
At variance with F3061-24a, paragraph 4.4.2, use of system level verification is usually not acceptable, and it should be discussed with EASA.
- [F3230-25](#) Standard Practice for Safety Assessment of Systems and Equipment in Small Aircraft
For aircraft that are powered by electric motors, EASA has not yet accepted Table 3 of F3230-25, and its use should be discussed with EASA.
- [F3227/F3227M-25](#) Standard Specification for Environmental Systems in Aircraft
At variance with F3227-25, Oxygen Fire Hazards Analysis is not completely covered in current ASTM standards. At variance, additional means of compliance have been developed by EASA for the specific application

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2510 Equipment, systems, and installations

ED Decision 2017/025/R

CS-23 Amdt 4

23.1309 Equipment, systems, and installations

23.1323 Airspeed indicating system

23.1325 Static pressure system

23.1329 Automatic pilot system

23.1331(b), (c) Instruments using a power source

23.1335 Flight director systems

23.1337(b), (c) Powerplant instruments installation

23.1357 Circuit protective devices

23.1431 Electronic equipment

23.1437 Accessories for twin-engine aeroplanes

23.672(c) Stability augmentation and automatic and power-operated systems

23.677(d) Trim systems

23.701 Flap interconnection

23.735(d) Brakes

23.775(g) Windshields and windows

23.831(d) Ventilation

23.841(b)(8), (c), (d)(2), (d)(3) Pressurised cabins

AMC3 23.2510 Equipment, systems, and installations

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.1309 Equipment, systems, and installations

VLA.1323 Airspeed indicating system

VLA.1325 Static pressure system

VLA.1331 Instruments using a power supply

VLA.1337 Powerplant instruments

VLA.1357 Circuit protective devices

VLA.1431 Electronic equipment

VLA.677 Trim systems

VLA.701 Flap interconnection

VLA.735 Brakes

VLA.775 Windshields and windows

VLA.831 Ventilation

CS 23.2515 Electrical and electronic system lightning protection

ED Decision 2023/002/R

For an aeroplane where the exposure to lightning is likely:

- (a) each electrical or electronic system that performs a function, the failure of which would prevent the continued safe flight and landing of the aeroplane, must be designed and installed such that:
 - (1) the function at the aeroplane level is not adversely affected during and after the time the aeroplane is exposed to lightning; and
 - (2) the system recovers normal operation of that function in a timely manner after the aeroplane is exposed to lightning unless the system's recovery conflicts with other operational or functional requirements of the system;

- (b) each electrical and electronic system that performs a function, the failure of which would reduce the capability of the aeroplane or the ability of the flight crew to respond to an adverse operating condition, must be designed and installed such that the system recovers normal operation of that function in a timely manner after the aeroplane is exposed to lightning.

AMC1 23.2515 Electrical and electronic system lightning protection

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

9.4 Electrical and Electronic System Lightning Protection

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3367-23](#) Standard Practice for Simplified Methods for Addressing High Intensity Radiated Fields (HIRF) and Indirect Effects of Lightning on Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2515 Electrical and electronic system lightning protection

ED Decision 2017/025/R

CS-23 Amdt 4

23.1306 Electrical and electronic system lightning protection

AMC3 23.2515 Electrical and electronic system lightning protection

ED Decision 2017/025/R

None

CS 23.2520 High-intensity radiated fields (HIRF) protection

ED Decision 2017/013/R

- (a) Each electrical and electronic system that perform a function, the failure of which would prevent the continued safe flight and landing of the aeroplane, must be designed and installed such that:
- (1) the function at the aeroplane level is not adversely affected during and after the time the aeroplane is exposed to the HIRF environment; and
 - (2) the system recovers normal operation of that function in a timely manner after the aeroplane is exposed to the HIRF environment, unless the system's recovery conflicts with other operational or functional requirements of the system.
- (b) For aeroplanes approved for instrument flight rules (IFR) operations, each electrical and electronic system that performs a function, the failure of which would reduce the capability of the aeroplane or the ability of the flight crew to respond to an adverse operating condition, must be designed and installed such that the system recovers normal operation of that function in a timely manner after the aeroplane is exposed to the HIRF environment.

AMC1 23.2520 High-intensity radiated fields (HIRF) protection

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

9.5 High-Intensity Radiated Fields (HIRF) Protection

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft[F3236-21a](#) Standard Specification for High Intensity Radiated Field (HIRF) Protection in Small Aircraft[F3367-23](#) Standard Practice for Simplified Methods for Addressing High Intensity Radiated Fields (HIRF) and Indirect Effects of Lightning on Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2520 High-intensity radiated fields (HIRF) protection

ED Decision 2017/025/R

CS-23 Amdt 4

23.1308 High-Intensity Radiated Fields (HIRF) protection

AMC3 23.2520 High-intensity radiated fields (HIRF) protection

ED Decision 2017/025/R

None

CS 23.2525 System power generation, storage, and distribution

ED Decision 2017/013/R

The power generation, storage, and distribution for any system must be designed and installed to:

- (a) supply the power required for operation of connected loads during all intended operating conditions;
- (b) ensure no single failure or malfunction will prevent the system from supplying the essential loads required for continued safe flight and landing; and
- (c) have enough capacity, if the primary source fails, to supply essential loads, including non-continuous essential loads for the time needed to complete the function, required for safe flight and landing.

AMC1 23.2525 System power generation, storage, and distribution

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

9.6 System Power Generation, Storage, and Distribution

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft[F3231/F3231M-24](#) Standard Specification for Electrical Systems for Aircraft with Combustion Engine Electrical Power Generation[F2490-20](#) Standard Guide for Aircraft Electrical Load and Power Source Capacity Analysis

[F3233/F3233M-23b](#) Standard Specification for Flight and Navigation Instrumentation in Aircraft

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

[F3120/F3120M-20](#) Standard Specification for Ice Protection for General Aviation Aircraft

Remarks

ASTM F44 published standards for showing compliance for electrical systems that are installed on aeroplanes with electric or hybrid-electric propulsion systems. EASA has not yet accepted [F3316-19](#); however, EASA would take into consideration applications from applicants that use this standard as the basis for the development of their means of compliance subject to agreement with EASA.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2525 System power generation, storage, and distribution

ED Decision 2023/002/R

CS-23 Amdt 4

23.1303 Flight and navigation instruments

23.1331(b), (c) Instruments using a power source

23.1351(a), (b), (c) Electrical Systems – General

23.1353 Storage battery design and installation

23.1357 Circuit protective devices

Remarks

At variance with CS 23.1357(b) and (d), EASA does not accept a protective device for a circuit essential to flight safety in designs applications after the date of entry into force of the AMC & GM to CS-23 Issue 4; automatic fuses or circuit breakers should be used instead.

AMC3 23.2525 System power generation, storage, and distribution

ED Decision 2023/002/R

CS-VLA Amdt 1

VLA 1303 Flight and navigation instruments

VLA 1331 Instruments using a power supply

VLA 1351 Electrical Systems – General

VLA 1353 Storage battery design and installation

VLA 1357 Circuit protective devices

Remarks

At variance with CS-VLA 1357(b) and (d), EASA does not accept a protective device for a circuit essential to flight safety in designs applications after the date of entry into force of the AMC & GM to CS-23 Issue 4; automatic fuses or circuit breakers should be used instead.

CS 23.2530 External and cockpit lighting

ED Decision 2017/013/R

- (a) The applicant must design and install all lights to minimise any adverse effects on the performance of flight crew duties.
- (b) Any position and anti-collision lights, if required by operational rules, must have the intensities, flash rate, colours, fields of coverage, and other characteristics to provide sufficient time for another aircraft to avoid a collision.
- (c) Any position lights, if required by operational rules, must include a red light on the left side of the aeroplane, a green light on the right side of the aeroplane, spaced laterally as far apart as practicable, and a white light facing aft, located on an aft portion of the aeroplane or on the wing tips.
- (d) Taxi and landing lights, if required, must be designed and installed so they provide sufficient light for night operations.
- (e) For seaplanes or amphibian aeroplanes, riding lights must provide a white light visible in clear atmospheric conditions.

AMC1 23.2530 External and cockpit lighting

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification**9.7 External and Cockpit Lighting**[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft[F3233/F3233M-23b](#) Standard Specification for Flight and Navigation Instrumentation in Aircraft[F3234/F3234M-21](#) Standard Specification for Exterior Lighting in Small Aircraft[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft[F3120/F3120M-20](#) Standard Specification for Ice Protection for General Aviation Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2530 External and cockpit lighting

ED Decision 2017/025/R

CS-23 Amdt 4

23.1381 Instrument lights

23.1383(a), (b), (c) Taxi and landing lights

23.1385(a), (b), (c) Position light system installation

23.1387 Position light system dihedral angles

- 23.1391 Minimum intensities in the horizontal plane of position lights
- 23.1393 Minimum intensities in any vertical plane of position lights
- 23.1395 Maximum intensities in overlapping beams of position lights
- 23.1397 Colour specifications
- 23.1399 Riding light
- 23.1401 Anti-collision light system

AMC3 23.2530 External and cockpit lighting

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.1384 External lights

CS 23.2535 Safety equipment

ED Decision 2017/013/R

Safety and survival equipment, required by the operating rules, must be reliable, readily accessible, easily identifiable, and clearly marked to identify its method of operation.

AMC1 23.2535 Safety equipment

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

9.8 Safety Equipment

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3083/F3083M-20a](#) Standard Specification for Emergency Conditions, Occupant Safety and Accommodations

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2535 Safety equipment

ED Decision 2017/025/R

CS-23 Amdt 4

23.1411 Safety Equipment-General

23.1415 Ditching equipment

AMC3 23.2535 Safety equipment

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.1411 Safety Equipment-General

CS 23.2540 Flight in icing conditions

ED Decision 2017/013/R

An applicant who requests certification for flight in icing conditions must show the following in the icing conditions for which certification is requested:

- (a) the ice protection system provides for safe operation; and
- (b) the aeroplane design must provide protection from stalling when the autopilot is operating.

AMC1 23.2540 Flight in icing conditions

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

9.9 Flight in Icing Conditions

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3233/F3233M-23b](#) Standard Specification for Flight and Navigation Instrumentation in Aircraft

[F3120/F3120M-20](#) Standard Specification for Ice Protection for General Aviation Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2540 Flight in icing conditions

ED Decision 2023/002/R

CS-23 Amdt 4

23.1323 Airspeed indicating system

23.1325(b), (g) Static pressure system

23.775(f) Windshields and windows

Remarks

Following the cancellation of FAA AC-1419-2D, applicants should now use the icing conditions that are outlined in [AMC1 23.2165](#).

AMC3 23.2540 Flight in icing conditions

ED Decision 2017/025/R

None

CS 23.2545 Pressurised systems elements

ED Decision 2017/013/R

Pressurised systems must withstand appropriate proof and burst pressures.

AMC1 23.2545 Pressurised systems elements

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

9.10 Pressurized System Elements

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3229/F3229M-23a](#) Standard Practice for Static Pressure System Tests in Small Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2545 Pressurised systems elements

ED Decision 2017/025/R

CS-23 Amdt 4

23.1438 Pressurization and pneumatic systems

23.1435(a)(4), (b) Hydraulic Systems

23.1453 Protection of oxygen equipment from rupture

AMC3 23.2545 Pressurised systems elements

ED Decision 2017/025/R

None

CS 23.2550

ED Decision 2017/013/R

(reserved)

CS 23.2555 Installation of recorders (e.g. cockpit voice recorders and flight data recorders)

ED Decision 2017/013/R

If recording is required by the operating rules, the system:

- (a) is installed so as to ensure accurate and intelligible recording and safeguarding of the required data, also in conditions encountered during crash, water immersion or fire;
- (b) is powered by the most reliable power source and remains powered for as long as possible without jeopardising service to essential or emergency loads and emergency operation of the aeroplane;
- (c) includes features to facilitate the localisation of a memory medium after an accident; and
- (d) is installed so that it automatically records when the aeroplane is capable of moving under its own power.

AMC1 23.2555 Installation of recorders (e.g. cockpit voice recorders and flight data recorders)

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

9.12 Installation of Cockpit recorders

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3228-21](#) Standard Specification for Flight Data and Voice Recording in Small Aircraft

9.13 Installation of Flight Data Recorders:

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3228-21](#) Standard Specification for Flight Data and Voice Recording in Small Aircraft

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2555 Installation of recorders (e.g. cockpit voice recorders and flight data recorders)

ED Decision 2017/025/R

CS-23 Amdt 4

23.1457 Cockpit voice recorders

23.1459 Flight recorders

AMC3 23.2555 Installation of recorders (e.g. cockpit voice recorders and flight data recorders)

ED Decision 2017/025/R

None

SUBPART G — FLIGHT CREW INTERFACE AND OTHER INFORMATION

CS 23.2600 Flight crew compartment

ED Decision 2017/013/R

- (a) The pilot compartment arrangement, including pilot view, and its equipment must allow the flight crew to perform their duties within the operating envelope of the aeroplane, without excessive concentration, skill, alertness, or fatigue.
- (b) The applicant must install flight, navigation, surveillance, and powerplant installation controls and displays so that a qualified flight crew can monitor and perform defined tasks associated with the intended functions of systems and equipment. The system and equipment design must minimise flight crew errors, which could result in additional hazards.
- (c) For Level-4 aeroplanes, the flight crew interface design must allow for continued safe flight and landing after the loss of vision through any one of the windshield panels.

AMC1 23.2600 Flight crew compartment

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

10.1 Flight Crew Compartment Interface

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3232/F3232M-25](#) Standard Specification for Flight Controls in Small Aircraft

[F3062/F3062M-20](#) Standard Specification for Aircraft Powerplant Installation

[F3063/F3063M-21](#) Standard Specification for Aircraft Fuel Storage and Delivery

[F3064/F3064M-21](#) Standard Specification for Aircraft Powerplant Control, Operation, and Indication

[F3114-21](#) Standard Specification for Structures

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

Remarks

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

Hydrophobic coating is not completely covered in current ASTM standards. At variance, additional means of compliance have been developed by EASA for this specific application.

ASTM F3264-24 does not contain standards that ensure that the required pilot compartment view is provided in conditions of fog or frost formation on the internal portion of the windshield and side windows. Pilot compartment view with formation of fog or frost must be addressed in showing compliance with [CS 23.2600\(a\)](#). Applicants may use the provisions of CS 23.773(b) at Amendment 4 as a means of complying with this aspect of [CS 23.2600\(a\)](#), or may propose a different means of compliance in accordance with [CS 23.2010](#).

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2600 Flight crew compartment

ED Decision 2017/025/R

CS-23 Amdt 4

23.671 Control systems - General

23.677(a) Trim systems

23.699 Wing flap position indicator

23.729(e) Landing gear extension and retraction system

23.745 Nose/Tail wheel steering

23.771(a) Pilot compartment

23.773 Pilot compartment view

23.775(e), (h)(2) Windshields and windows

23.777 Cockpit controls

23.779 Motion and effect of cockpit controls

23.781 Cockpit control knob shape

23.831(c) Ventilation

23.1141(g) Powerplant controls: general

23.1142 Auxiliary power unit controls

23.1143(a) through (f) Engine controls

23.1145 Ignition switches

23.1147 Mixture controls

23.1149 Propeller speed and pitch controls

23.1153 Propeller feathering controls

23.1155 Turbine engine reverse thrust and propeller pitch settings below the flight regime

23.1157 Carburettor air temperature controls

23.1203(d) Fire detector system

23.1329(d) Automatic pilot system

23.1335 Flight director systems

23.1367 Switches

23.1381(a), (b) Instrument lights

23.1419(d) Ice protection

23.1435(a)(2) Hydraulic Systems

23.1523 Minimum Flight Crew

AMC3 23.2600 Flight crew compartment

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.671 Control systems - General
VLA.677 Trim systems
VLA.699 Wing flap position indicator
VLA.729 Landing gear extension and retraction system
VLA.745 Nose/Tail wheel steering
VLA.771 Pilot compartment
VLA.773 Pilot compartment view
VLA.775 Windshields and windows
VLA.777 Cockpit controls
VLA.779 Motion and effect of cockpit controls
VLA.781 Cockpit control knob shape
VLA.831 Ventilation
VLA.1141 Powerplant controls: general
VLA.1143 Engine controls
VLA.1145 Ignition switches
VLA.1147 Mixture controls
VLA.1367 Switches

CS 23.2605 Installation and operation information

ED Decision 2017/013/R

- (a) Each item of installed equipment related to the flight crew interface must be labelled, if applicable, as for its identification, function, or operating limitations, or any combination of these factors.
- (b) There must be a discernible means of providing system operating parameters required to operate the aeroplane, including warnings, cautions, and normal indications, to the responsible crew member.
- (c) Information concerning an unsafe system operating condition must be provided in a timely manner to the crew member responsible for taking corrective action. The information must be clear enough to avoid likely crew member errors.
- (d) Information related to safety equipment is easily identifiable and its method of operation is clearly marked.

AMC1 23.2605 Installation and operation information

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

10.2 Installation and Operation Information

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3232/F3232M-25](#) Standard Specification for Flight Controls in Small Aircraft

[F3233/F3233M-23b](#) Standard Specification for Flight and Navigation Instrumentation in Aircraft

[F3231/F3231M-24](#) Standard Specification for Electrical Systems for Aircraft with Combustion Engine Electrical Power Generation

[F3062/F3062M-20](#) Standard Specification for Aircraft Powerplant Installation

[F3063/F3063M-21](#) Standard Specification for Aircraft Fuel Storage and Delivery

[F3064/F3064M-21](#) Standard Specification for Aircraft Powerplant Control, Operation, and Indication

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

[F3120/F3120M-20](#) Standard Specification for Ice Protection for General Aviation Aircraft

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

Remarks

[F3227/F3227M-25](#) Standard Specification for Environmental Systems in Aircraft

At variance with F3227-25, Oxygen Fire Hazards Analysis is not completely covered in current ASTM standards. At variance, additional means of compliance have been developed by EASA for this specific application.

[AMC & GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2605 Installation and operation information

ED Decision 2019/020/R

CS-23 Amdt 4

23.671(b) Control systems - General

23.672(a) Stability augmentation and automatic and power-operated systems

23.679(a), (b) Control system locks

23.703 Take-off warning system

23.729(f) Landing gear extension and retraction system

23.783(e)(3) Doors

23.841(b)(5), (b)(6), (d)(4), (d)(5) Pressurised cabins

23.991(c) Fuel pumps

23.1142 Auxiliary power unit controls

23.1301(b) Function and installation

23.1305 Powerplant instruments
23.1309(d) Equipment, systems, and installations
23.1322 Warning, caution and advisory lights
23.1326 Pitot heat indication systems
23.1329(h) Automatic pilot system
23.1331(a) Instruments using a power source
23.1335 Flight director systems
23.1337(b), (d) Powerplant instruments installation
23.1351(c), (d) Electrical Systems - General
23.1416(c) Pneumatic de-icer boot system
23.1441(c) Oxygen Equipment and supply
23.1561 Safety equipment

Remarks

23.1305 must be complemented. F3064-18 § 6.2.1.6 provides this AMC.

AMC3 23.2605 Installation and operation information*ED Decision 2019/020/R***CS VLA Amdt 1**

VLA.671 Control systems - General
VLA.679 Control system locks
VLA.729 Landing gear extension and retraction system
VLA.783 Doors
VLA.991 Fuel pumps
VLA.1301 Function and installation
VLA.1305 Powerplant instruments
VLA.1309 Equipment, systems, and installations
VLA.1322 Warning, caution and advisory lights
VLA.1331 Instruments using a power supply
VLA.1337 Powerplant instruments
VLA.1351 Electrical Systems - General
VLA.1561 Safety equipment

Remarks

VLA.1305 must be complemented. F3064-18 § 6.2.1.6 provides this AMC.

CS 23.2610 Instrument markings, control markings and placards

ED Decision 2017/013/R

- (a) Each aeroplane must display in a conspicuous manner any placard and instrument marking necessary for operation.
- (b) The design must clearly indicate the function of each cockpit control, other than primary flight controls.
- (c) The applicant must include instrument marking and placard information in the Aeroplane Flight Manual.

AMC1 23.2610 Instrument markings, control markings and placards

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification*10.3 Instrument Markings, Control Markings, and Placards*[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft[F3063/F3063M-21](#) Standard Specification for Aircraft Fuel Storage and Delivery[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft[F3120/F3120M-20](#) Standard Specification for Ice Protection for General Aviation Aircraft[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

[AMC&GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2610 Instrument markings, control markings and placards

ED Decision 2017/025/R

CS-23 Amdt 4

23.733 Tires

23.777 Cockpit controls

23.841(b)(7) Pressurised cabins

23.1001(g) Fuel jettisoning system

23.1321 Arrangement and visibility

23.1337(d) Powerplant instruments installation

23.1450(c) Chemical oxygen generators

23.1501 General

23.1505 Airspeed limitations

23.1507 Operating manoeuvring speed

23.1511 Flap extended speed

23.1513 Minimum control speed

23.1519 Weight and center of gravity

- 23.1521 Powerplant limitations
- 23.1522 Auxiliary power unit limitations
- 23.1523 Minimum flight crew
- 23.1524 Maximum passenger seating configuration
- 23.1525 Kinds of operation
- 23.1527 Maximum operating altitude
- 23.1541 Marking and Placards - General
- 23.1543 Instrument marking: general
- 23.1545 Airspeed indicator
- 23.1547 Magnetic direction indicator
- 23.1549 Powerplant and auxiliary power unit instruments
- 23.1551 Oil quantity indicator
- 23.1553 Fuel quantity indicator
- 23.1555 Control markings
- 23.1557 Miscellaneous marking and placards
- 23.1559 Operating limitations placard
- 23.1561 Safety equipment
- 23.1563 Airspeed placards
- 23.1567 Flight manoeuvre placard

AMC3 23.2610 Instrument markings, control markings and placards

ED Decision 2017/025/R

CS VLA Amdt 1

- VLA.777 Cockpit controls
- VLA.1321 Arrangement and visibility
- VLA.1337 Powerplant instruments
- VLA.1501 General
- VLA.1505 Airspeed limitations
- VLA.1507 Manoeuvring speed
- VLA.1511 Flap extended speed
- VLA.1519 Weight and center of gravity
- VLA.1521 Powerplant limitations
- VLA.1525 Kinds of operation
- VLA.1541 Marking and Placards - General
- VLA.1543 Instrument marking: general

VLA.1545 Airspeed indicator
VLA.1547 Magnetic direction indicator
VLA.1549 Powerplant instruments
VLA.1551 Oil quantity indicator
VLA.1555 Control markings
VLA.1557 Miscellaneous marking and placards
VLA.1559 Operating limitations placard
VLA.1561 Safety equipment

CS 23.2615 Flight, navigation, and powerplant instruments

ED Decision 2017/013/R

- (a) Installed systems must provide the flight crew member who sets or monitors parameters for the flight, navigation, and powerplant the information necessary to do so during each phase of flight. This information must:
 - (1) be presented in a manner that the crew members can monitor the parameters and trends, as needed to operate the aeroplane; and
 - (2) include limitations, unless the limitation cannot be exceeded in all intended operations.
- (b) Indication systems that integrate the display of flight or powerplant parameters required to safely operate the aeroplane, or required by the operating rules, must:
 - (1) not inhibit the primary display of flight or powerplant parameters needed by any flight crew member in any normal mode of operation; and
 - (2) in combination with other systems, be designed and installed so information essential for continued safe flight and landing will be available to the flight crew in a timely manner after any single failure or probable combination of failures.

AMC1 23.2615 Flight, navigation, and powerplant instruments

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

10.4 Flight, Navigation, and Powerplant Instruments

[F3061/F3061M-24a](#) Standard Specification for Systems and Equipment in Small Aircraft

[F3062/F3062M-20](#) Standard Specification for Aircraft Powerplant Installation

[F3064/F3064M-21](#) Standard Specification for Aircraft Powerplant Control, Operation, and Indication

[F3432-20a](#) Standard Practice for Powerplant Instruments

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

[AMC&GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2615 Flight, navigation, and powerplant instruments

ED Decision 2026/003/R

CS-23 Amdt 4

- 23.1141(g) Powerplant controls: general
- 23.1142 Auxiliary power unit controls
- 23.1303 Flight and navigation instruments
- 23.1305 Powerplant instruments
- 23.1311 Electronic display instrument systems
- 23.1323 Airspeed indicating system
- 23.1325 Static pressure system
- 23.1327 Magnetic direction indicator
- 23.1337 Powerplant instruments installation

[AMC&GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC3 23.2615 Flight, navigation, and powerplant instruments

ED Decision 2026/003/R

CS-VLA Amdt 1

- VLA 1141 Powerplant controls— general
- VLA 1303 Flight and navigation instruments
- VLA 1305 Powerplant instruments
- VLA 1323 Airspeed indicating system
- VLA 1325 Static pressure system
- VLA 1327 Magnetic direction indicator
- VLA 1337 Powerplant instruments

[AMC&GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

CS 23.2620 Aeroplane Flight Manual

ED Decision 2017/013/R

The applicant must provide an aeroplane flight manual that must be delivered with each aeroplane and contains the following information:

- (a) operating limitations and procedures;
- (b) performance information;
- (c) loading information;

- (d) instrument marking and placard information; and
- (e) any other information necessary for the safe operation of the aeroplane.

AMC1 23.2620 Aeroplane Flight Manual

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

10.5 Aeroplane Flight Manual

[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft

[F3174/F3174M-21](#) Standard Specification for Establishing Operating Limitations and Information for Aeroplanes

[F3120/F3120M-20](#) Standard Specification for Ice Protection for General Aviation Aircraft

[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

[AMC&GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2620 Aeroplane Flight Manual

ED Decision 2017/025/R

CS-23 Amdt 4

23.1581 Airplane Flight Manual and Approved Manual Material - General

23.1583 Operating limitations

23.1585 Operating procedures

23.1587 Performance information

23.1589 Loading information

AMC3 23.2620 Aeroplane Flight Manual

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.1581 Airplane Flight Manual and Approved Manual Material - General

VLA.1583 Operating limitations

VLA.1585 Operating procedures

VLA.1587 Performance information

VLA.1589 Loading information

CS 23.2625 Instructions for Continued Airworthiness

ED Decision 2017/013/R

- (a) The applicant must prepare Instructions for Continued Airworthiness that are appropriate for the certification level and performance level of the aeroplane.
- (b) If Instructions for Continued Airworthiness are not supplied by the manufacturer of an appliance or product installed in the aeroplane, the Instructions for Continued Airworthiness for the aeroplane must include the information essential to the continued airworthiness of the aeroplane.
- (c) The Instructions for Continued Airworthiness must contain a Section titled 'Airworthiness limitations' that is segregated and clearly distinguishable from the rest of the document. This Section must set forth each mandatory replacement time, structural inspection interval, and related structural inspection procedure required for type certification. This Section must contain a legible statement in a prominent location that reads: 'The Airworthiness limitations Section is approved and variations must also be approved'.
- (d) The applicant must develop and implement procedures to prevent structural failures due to foreseeable causes of strength degradation, which could result in serious or fatal injuries, loss of the aeroplane, or extended periods of operation with reduced safety margins. The Instructions for Continued Airworthiness must include procedures developed under [CS 23.2255](#).

AMC1 23.2625 Instructions for Continued Airworthiness

ED Decision 2026/003/R

ASTM F44 F3264 Standard Specification for Normal Category Aeroplanes Certification

10.6 Instructions for Continued Airworthiness

[F3120/F3120M-20](#) Standard Specification for Ice Protection for General Aviation Aircraft[F3117/F3117M-24a](#) Standard Specification for Crew Interface in Aircraft[F3408/F3408M-21](#) Standard Specification for Aircraft Emergency Parachute Recovery Systems

[AMC&GM to CS-23: Issue 4]

[AMC & GM to CS-23: Issue 5]

AMC2 23.2625 Instructions for Continued Airworthiness

ED Decision 2017/025/R

CS-23 Amdt 4

23.1529 Instructions for Continued Airworthiness (With Appendix G)

AMC3 23.2625 Instructions for Continued Airworthiness

ED Decision 2017/025/R

CS VLA Amdt 1

VLA.1529 Instructions for Continued Airworthiness